

# TK Series

Designed for tough industrial environments and a wide variety of applications, TK Enclosures are available with standard gray or tinted transparent covers in several heights. Sidewalls and endwalls are supplied smooth or with knockouts. Precision molded from impact and flame resistant materials, they offer functionality and appealing solutions for diverse application requirements.

- 13 different enclosures with up to 3 different cover heights
- IP66 (NEMA 4X)
- Polystyrene or Polycarbonate
- Gray or tinted transparent covers
- Smooth sidewalls or sidewalls with knockouts
- Four cover mounting screws
- Tongue and groove with polyurethane gasket (CFC free)
- Gasket inserted by robots
- HF - EMC models available
- Knockout mounting holes in enclosure base
- Screw fastening cover design requires six turns to lock
- Dust and moisture proof
- Non flammable and halogen free

# TK Series Enclosures

## Enclosure Mounting

**Altech/spelsberg** Enclosures can be mounted directly onto a panel, frame or other mounting surface through corner mounting holes, knockout holes molded into the base, or with optional mounting flanges. Sealing caps for base mounted screws included.

**Note:** Corner hole mounting is required to maintain the NEMA 4X rating on TK and EK Enclosures.



## Conduit Connectors

Conduit connectors are available in Pg or NPT sizes. They are installed into standard knockouts or custom drilled holes and are secured with locknuts.



## Customization

Our enclosures can be factory supplied with custom openings. Using state of the art machining, we can punch, drill, mill or cut to your most exacting specifications. We customize quickly and accurately, ... at a reasonable cost!

EMI/RFI shielding is also available to protect sensitive electronic components.



**Standard Features**

- **Protection Level:** IP66 (NEMA 4X)
- **Technical:** Smooth Sidewalls  
1 Sidewall Knockout or Integral Cable Gland (5-10mm cable diameter)  
Gray or Clear Transparent Cover
- **Enclosure Material:** Polystyrene or Polycarbonate
- **Gasket Material:** Polyurethane
- **Color:** Light Gray
- **Temperature Range:** Polystyrene  
-40°C to 70°C (-40°F to 158°F)  
Polycarbonate  
-35°C to 120°C (-31°F to 248°F)
- **Accessories:** See section below



**TK55**

**Polystyrene**

**Polycarbonate**

| Ordering Information               | Height mm (in)  | Cat. No. | Type       | Cover Color | Std. Pk. | Cat. No. | Type       | Cover Color | Std. Pk. |
|------------------------------------|-----------------|----------|------------|-------------|----------|----------|------------|-------------|----------|
| ☐ Enclosure - smooth sidewall      | 35 mm (1.38 in) | 110-455  | PS 55-4-o  | gray        | 5        | 120-455  | PC55-4-o   | gray        | 5        |
| ☐ Enclosure - smooth sidewall      | 35 mm (1.38 in) | 111-455  | PS 55-4-to | trans.      | 5        | 130-455  | PC55-4-to  | trans.      | 5        |
| ☐ Enclosure - metric knockout      | 35 mm (1.38 in) | 105-455  | PS 55-4-m  | gray        | 5        | 127-455  | PC 55-4-m  | gray        | 5        |
| ☐ Enclosure - metric knockout      | 35 mm (1.38 in) | 106-455  | PS 55-4-tm | trans.      | 5        | 137-455  | PC 55-4-tm | trans.      | 5        |
| ☐ Enclosure - Integral Cable Gland | 35 mm (1.38 in) | 145-455  | PS 55-4-v  | gray        | 5        | 129-455  | PC 55-4-v  | gray        | 5        |
| ☐ Enclosure - Integral Cable Gland | 35 mm (1.38 in) | 146-455  | PS 55-4-tv | trans.      | 5        | 139-455  | PC 55-4-tv | trans.      | 5        |

**TK75**

**Polystyrene**

**Polycarbonate**

| Ordering Information               | Height mm (in)  | Cat. No. | Type       | Cover Color | Std. Pk. | Cat. No. | Type       | Cover Color | Std. Pk. |
|------------------------------------|-----------------|----------|------------|-------------|----------|----------|------------|-------------|----------|
| ☐ Enclosure - smooth sidewall      | 35 mm (1.38 in) | 110-475  | PS 75-4-o  | gray        | 5        | 120-475  | PC75-4-o   | gray        | 5        |
| ☐ Enclosure - smooth sidewall      | 35 mm (1.38 in) | 111-475  | PS 75-4-to | trans.      | 5        | 130-475  | PC75-4-to  | trans.      | 5        |
| ☐ Enclosure - metric knockout      | 35 mm (1.38 in) | 105-475  | PS 75-4-m  | gray        | 5        | 127-475  | PC 75-6-m  | gray        | 5        |
| ☐ Enclosure - metric knockout      | 35 mm (1.38 in) | 106-475  | PS 75-4-tm | trans.      | 5        | 137-475  | PC 75-8-tm | trans.      | 5        |
| ☐ Enclosure - Integral Cable Gland | 35 mm (1.38 in) | 145-475  | PS 75-4-v  | gray        | 5        | 129-475  | PC 75-8-v  | gray        | 5        |
| ☐ Enclosure - Integral Cable Gland | 35 mm (1.38 in) | 146-475  | PS 75-4-tv | trans.      | 5        | 139-475  | PC 75-8-tv | trans.      | 5        |

**Accessories**


| Ordering Information  | Cat. No. | Type   | Std. Pk. |
|-----------------------|----------|--------|----------|
| Mounting Plate (TK55) | 195-055  | MP55   | 1        |
| Mounting Plate (TK75) | 195-075  | MP75   | 1        |
| PCB Bracket           | 194-110  | MP/LPH | 2        |
| Mounting Bracket      | 194-002  | MB     | 1        |

Please refer to pages 106-113 for additional accessories and detailed information.

# TK 77 – Polystyrene and Polycarbonate – 65x65mm (2.56x2.56in.)

## Standard Features

- **Protection Level:** IP66 (NEMA 4X)
- **Technical:** Smooth or Knockout Sidewalls  
Gray or Tinted Transparent Cover <sup>①</sup>  
Multiple Enclosure Mounting Options
- **Enclosure Material:** Polystyrene or Polycarbonate
- **Gasket Material:** Polyurethane
- **Color:** Light Gray
- **Temperature Range:** Polystyrene  
-40°C to 70°C (-40°F to 158°F)  
Polycarbonate  
-35°C to 120°C (-31°F to 248°F)
- **Accessories:** See section below



## Smooth Sidewalls

| Ordering Information   | Height mm (in)  | Polystyrene |            |             |          | Polycarbonate |            |             |          |
|------------------------|-----------------|-------------|------------|-------------|----------|---------------|------------|-------------|----------|
|                        |                 | Cat. No.    | Type       | Cover Color | Std. Pk. | Cat. No.      | Type       | Cover Color | Std. Pk. |
| Enclosure - low cover  | 57 mm (2.24 in) | 110-401     | PS 77-6-o  | gray        | 5        | 120-401       | PC 77-6-o  | gray        | 5        |
| Enclosure - high cover | 81 mm (3.19 in) | 110-901     | PS 77-8-o  | gray        | 5        | 120-901       | PC 77-8-o  | gray        | 5        |
| Enclosure - low cover  | 57 mm (2.24 in) | 111-001     | PS 77-6-to | trans.      | 5        | 130-001       | PC 77-6-to | trans.      | 5        |
| Enclosure - high cover | 81 mm (3.19 in) | 111-501     | PS 77-8-to | trans.      | 5        | 130-501       | PC 77-8-to | trans.      | 5        |

## Sidewalls with PG Knockouts (metric available)

| Ordering Information   | Height mm (in)  | Polystyrene |           |             |          | Polycarbonate |           |             |          |
|------------------------|-----------------|-------------|-----------|-------------|----------|---------------|-----------|-------------|----------|
|                        |                 | Cat. No.    | Type      | Cover Color | Std. Pk. | Cat. No.      | Type.     | Cover Color | Std. Pk. |
| Enclosure - low cover  | 57 mm (2.24 in) | 115-401     | PS 77-6   | gray        | 5        | 125-401       | PC 77-6   | gray        | 5        |
| Enclosure - high cover | 81 mm (3.19 in) | 115-901     | PS 77-8   | gray        | 5        | 125-901       | PC 77-8   | gray        | 5        |
| Enclosure - low cover  | 57 mm (2.24 in) | 116-001     | PS 77-6-t | trans.      | 5        | 135-001       | PC 77-6-t | trans.      | 5        |
| Enclosure - high cover | 81 mm (3.19 in) | 116-501     | PS 77-8-t | trans.      | 5        | 135-501       | PC 77-8-t | trans.      | 5        |

## Accessories


| Ordering Information | Cat. No. | Type       | Std. Pk. |
|----------------------|----------|------------|----------|
| Mounting Plate       | 195-001  | MP77       | 1        |
| DIN Rail TS15-49.5mm | Z-629    | TS 15/49.5 | 1        |
| Hinge Kit Set        | 190-002  | HK1        | 1        |
| Mounting Tab Kit     | 194-001  | MT1        | 1        |

Please refer to pages 106-113 for additional accessories and detailed information.

<sup>①</sup> Clear transparent lids available upon request

## Standard Features

- **Protection Level:** IP66 (NEMA 4X)
- **Technical:** Smooth or Knockout Sidewalls  
Gray or Tinted Transparent Cover <sup>①</sup>  
Multiple Enclosure Mounting Options
- **Enclosure Material:** Polystyrene or Polycarbonate
- **Gasket Material:** Polyurethane
- **Color:** Light Gray
- **Temperature Range:** Polystyrene  
-40°C to 70°C (-40°F to 158°F)  
Polycarbonate  
-35°C to 120°C (-31°F to 248°F)
- **Accessories:** See section below



### Smooth Sidewalls

#### Polystyrene

#### Polycarbonate

| Ordering Information     | Height mm (in)  | Cat. No. | Type       | Cover Color | Std. Pk. | Cat. No. | Type       | Cover Color | Std. Pk. |
|--------------------------|-----------------|----------|------------|-------------|----------|----------|------------|-------------|----------|
| ☐ Enclosure - low cover  | 57 mm (2.24 in) | 110-402  | PS 97-6-o  | gray        | 5        | 120-402  | PC 97-6-o  | gray        | 5        |
| ☐ Enclosure - high cover | 81 mm (3.19 in) | 110-902  | PS 97-8-o  | gray        | 5        | 120-902  | PC 97-8-o  | gray        | 5        |
| ☐ Enclosure - low cover  | 57 mm (2.24 in) | 111-002  | PS 97-6-to | trans.      | 5        | 130-002  | PC 97-6-to | trans.      | 5        |
| ☐ Enclosure - high cover | 81 mm (3.19 in) | 111-502  | PS 97-8-to | trans.      | 5        | 130-502  | PC 97-8-to | trans.      | 5        |

### Sidewalls with PG Knockouts (metric available)

#### Polystyrene

#### Polycarbonate

| Ordering Information     | Height mm (in)  | Cat. No. | Type      | Cover Color | Std. Pk. | Cat. No. | Type      | Cover Color | Std. Pk. |
|--------------------------|-----------------|----------|-----------|-------------|----------|----------|-----------|-------------|----------|
| ☐ Enclosure - low cover  | 57 mm (2.24 in) | 115-402  | PS 97-6   | gray        | 5        | 125-402  | PC 97-6   | gray        | 5        |
| ☐ Enclosure - high cover | 81 mm (3.19 in) | 115-902  | PS 97-8   | gray        | 5        | 125-902  | PC 97-8   | gray        | 5        |
| ☐ Enclosure - low cover  | 57 mm (2.24 in) | 116-002  | PS 97-6-t | trans.      | 5        | 135-002  | PC 97-6-t | trans.      | 5        |
| ☐ Enclosure - high cover | 81 mm (3.19 in) | 116-502  | PS 97-8-t | trans.      | 5        | 135-502  | PC 97-8-t | trans.      | 5        |

### RK Enclosures with Terminal Blocks

| Ordering Information               | Height          | Cat. No. | Type | Cover Color | Std. Pk. |
|------------------------------------|-----------------|----------|------|-------------|----------|
| Enclosure - 5 pole/12 AWG Terminal | 57 mm (2.24 in) | 605-404  | RK97 | gray        | 5        |
| Enclosure - DIN Rail only (TS15)   | 57 mm (2.24 in) | 605-904  | RK97 | gray        | 5        |

### Accessories


| Ordering Information | Cat. No. | Type     | Std. Pk. |
|----------------------|----------|----------|----------|
| Mounting Plate       | 195-002  | MP97     | 1        |
| DIN Rail TS15-80mm   | Z-630    | TS 15/80 | 1        |
| Hinge Kit Set        | 190-002  | HK1      | 1        |
| Mounting Tab Kit     | 194-001  | MT1      | 1        |

Please refer to pages 106-113 for additional accessories and detailed information.

<sup>①</sup> Clear transparent lids available upon request

## Standard Features

- **Protection Level:** IP66 (NEMA 4X)
- **Technical:** Smooth or Knockout Sidewalls  
Gray or Tinted Transparent Cover <sup>①</sup>  
Multiple Enclosure Mounting Options
- **Enclosure Material:** Polystyrene or Polycarbonate
- **Gasket Material:** Polyurethane
- **Color:** Light Gray
- **Temperature Range:** Polystyrene  
-40°C to 70°C (-40°F to 158°F)  
Polycarbonate  
-35°C to 120°C (-31°F to 248°F)
- **Accessories:** See section below



### Smooth Sidewalls

| Ordering Information   | Height mm (in)  | Polystyrene |            |             |          | Polycarbonate |            |             |          |
|------------------------|-----------------|-------------|------------|-------------|----------|---------------|------------|-------------|----------|
|                        |                 | Cat. No.    | Type       | Cover Color | Std. Pk. | Cat. No.      | Type       | Cover Color | Std. Pk. |
| Enclosure - low cover  | 57 mm (2.24 in) | 110-403     | PS 99-6-o  | gray        | 4        | 120-403       | PC 99-6-o  | gray        | 4        |
| Enclosure - high cover | 81 mm (3.19 in) | 110-903     | PS 99-8-o  | gray        | 3        | 120-903       | PC 99-8-o  | gray        | 3        |
| Enclosure - low cover  | 57 mm (2.24 in) | 111-003     | PS 99-6-to | trans.      | 4        | 130-003       | PC 99-6-to | trans.      | 4        |
| Enclosure - high cover | 81 mm (3.19 in) | 111-503     | PS 99-8-to | trans.      | 3        | 130-503       | PC 99-8-to | trans.      | 3        |

### Sidewalls with PG Knockouts (metric available)

| Ordering Information   | Height mm (in)  | Polystyrene |           |             |          | Polycarbonate |           |             |          |
|------------------------|-----------------|-------------|-----------|-------------|----------|---------------|-----------|-------------|----------|
|                        |                 | Cat. No.    | Type      | Cover Color | Std. Pk. | Cat. No.      | Type      | Cover Color | Std. Pk. |
| Enclosure - low cover  | 57 mm (2.24 in) | 115-403     | PS 99-6   | gray        | 4        | 125-403       | PC 99-6   | gray        | 4        |
| Enclosure - high cover | 81 mm (3.19 in) | 115-903     | PS 99-8   | gray        | 3        | 125-903       | PC 99-8   | gray        | 3        |
| Enclosure - low cover  | 57 mm (2.24 in) | 116-003     | PS 99-6-t | trans.      | 4        | 135-003       | PC 99-6-t | trans.      | 4        |
| Enclosure - high cover | 81 mm (3.19 in) | 116-503     | PS 99-8-t | trans.      | 3        | 135-503       | PC 99-8-t | trans.      | 3        |

### RK Enclosures with Terminal Blocks

| Ordering Information                | Height          | Cat. No. | Type | Cover Color | Std. Pk. |
|-------------------------------------|-----------------|----------|------|-------------|----------|
| Enclosure - 8 pole/12 AWG Terminal  | 57 mm (2.24 in) | 606-404  | RK99 | gray        | 4        |
| Enclosure - 10 pole/12 AWG Terminal | 57 mm (2.24 in) | 607-404  | RK99 | gray        | 4        |
| Enclosure - DIN Rail only (TS15)    | 57 mm (2.24 in) | 607-904  | RK99 | gray        | 4        |

### Accessories

| Ordering Information  | Cat. No. | Type     | Std. Pk. |
|-----------------------|----------|----------|----------|
| Mounting Plate        | 195-003  | MP99     | 1        |
| DIN Rail TS15 - 80 mm | Z-630    | TS 15/80 | 1        |
| Hinge Kit Set         | 190-002  | HK1      | 1        |
| Mounting Tab Kit      | 194-001  | MT1      | 1        |


Please refer to pages 106-113 for additional accessories and detailed information.

<sup>①</sup> Clear transparent lids available upon request

# TK 1111 – Polystyrene and Polycarbonate – 110x110mm (4.33x4.33in.)

## Standard Features

- **Protection Level:** IP66 (NEMA 4X)
- **Technical:** Smooth or Knockout Sidewalls  
Gray or Tinted Transparent Cover <sup>①</sup>  
Multiple Enclosure Mounting Options
- **Enclosure Material:** Polystyrene or Polycarbonate
- **Gasket Material:** Polyurethane
- **Color:** Light Gray
- **Temperature Range:** Polystyrene  
-40°C to 70°C (-40°F to 158°F)  
Polycarbonate  
-35°C to 120°C (-31°F to 248°F)
- **Accessories:** See section below



## Smooth Sidewalls

| Ordering Information   | Height mm (in)  | Polystyrene |              |             |          |          | Polycarbonate |             |          |  |
|------------------------|-----------------|-------------|--------------|-------------|----------|----------|---------------|-------------|----------|--|
|                        |                 | Cat. No.    | Type         | Cover Color | Std. Pk. | Cat. No. | Type          | Cover Color | Std. Pk. |  |
| Enclosure - low cover  | 66 mm (2.60 in) | 110-404     | PS 1111-7-o  | gray        | 3        | 120-404  | PC 1111-7-o   | gray        | 3        |  |
| Enclosure - high cover | 90 mm (3.54 in) | 110-904     | PS 1111-9-o  | gray        | 3        | 120-904  | PC 1111-9-o   | gray        | 3        |  |
| Enclosure - low cover  | 66 mm (2.60 in) | 111-004     | PS 1111-7-to | trans.      | 3        | 130-004  | PC 1111-7-to  | trans.      | 3        |  |
| Enclosure - high cover | 90 mm (3.54 in) | 111-504     | PS 1111-9-to | trans.      | 3        | 130-504  | PC 1111-9-to  | trans.      | 3        |  |

## Sidewalls with PG Knockouts (metric available)

| Ordering Information   | Height mm (in)  | Polystyrene |             |             |          |          | Polycarbonate |             |          |  |
|------------------------|-----------------|-------------|-------------|-------------|----------|----------|---------------|-------------|----------|--|
|                        |                 | Cat. No.    | Type        | Cover Color | Std. Pk. | Cat. No. | Type          | Cover Color | Std. Pk. |  |
| Enclosure - low cover  | 66 mm (2.60 in) | 115-404     | PS 1111-7   | gray        | 3        | 125-404  | PC 1111-7     | gray        | 3        |  |
| Enclosure - high cover | 90 mm (3.54 in) | 115-904     | PS 1111-9   | gray        | 3        | 125-904  | PC 1111-9     | gray        | 3        |  |
| Enclosure - low cover  | 66 mm (2.60 in) | 116-004     | PS 1111-7-t | trans.      | 3        | 135-004  | PC 1111-7-t   | trans.      | 3        |  |
| Enclosure - high cover | 90 mm (3.54 in) | 116-504     | PS 1111-9-t | trans.      | 3        | 135-504  | PC 1111-9-t   | trans.      | 3        |  |

## RK Enclosures with Terminal Blocks

| Ordering Information                | Height          | Cat. No. | Type   | Cover Color | Std. Pk. |
|-------------------------------------|-----------------|----------|--------|-------------|----------|
| Enclosure - 10 pole/10 AWG Terminal | 66 mm (2.60 in) | 609-404  | RK1111 | gray        | 3        |
| Enclosure - 12 pole/12 AWG Terminal | 66 mm (2.60 in) | 610-404  | RK1111 | gray        | 3        |
| Enclosure - DIN Rail only (TS35)    | 66 mm (2.60 in) | 610-906  | RK1111 | gray        | 3        |

## Accessories

| Ordering Information | Cat. No. | Type     | Std. Pk. |
|----------------------|----------|----------|----------|
| Mounting Plate       | 195-004  | MP1111   | 1        |
| DIN Rail TS35-81mm   | Z-650    | TS 35/81 | 1        |
| DIN Rail TS15-92mm   | Z-631    | TS 15/92 | 1        |
| Hinge Kit Set        | 190-002  | HK1      | 1        |
| Mounting Tab Kit     | 194-001  | MT1      | 1        |

Please refer to pages 106-113 for additional accessories and detailed information.

<sup>①</sup> Clear transparent lids available upon request

# TK 1309 – Polystyrene and Polycarbonate – 130x94mm (5.12x3.70in.)

## Standard Features

- **Protection Level:** IP66 (NEMA 4X)
- **Technical:** Smooth or Knockout Sidewalls  
Gray or Tinted Transparent Cover <sup>①</sup>  
Multiple Enclosure Mounting Options
- **Enclosure Material:** Polystyrene or Polycarbonate
- **Gasket Material:** Polyurethane
- **Color:** Light Gray
- **Temperature Range:** Polystyrene  
-40°C to 70°C (-40°F to 158°F)  
Polycarbonate  
-35°C to 120°C (-31°F to 248°F)
- **Accessories:** See section below



## Smooth Sidewalls

| Ordering Information   | Height mm (in)  | Polystyrene |              |             |          | Polycarbonate |              |             |          |
|------------------------|-----------------|-------------|--------------|-------------|----------|---------------|--------------|-------------|----------|
|                        |                 | Cat. No.    | Type         | Cover Color | Std. Pk. | Cat. No.      | Type         | Cover Color | Std. Pk. |
| Enclosure - low cover  | 57 mm (2.24 in) | 110-409     | PS 1309-6-o  | gray        | 3        | 120-409       | PC 1309-6-o  | gray        | 3        |
| Enclosure - high cover | 81 mm (3.19 in) | 110-909     | PS 1309-8-o  | gray        | 3        | 120-909       | PC 1309-8-o  | gray        | 3        |
| Enclosure - low cover  | 57 mm (2.24 in) | 111-009     | PS 1309-6-to | trans.      | 3        | 130-009       | PC 1309-6-to | trans.      | 3        |
| Enclosure - high cover | 81 mm (3.19 in) | 111-509     | PS 1309-8-to | trans.      | 3        | 130-509       | PC 1309-8-to | trans.      | 3        |

## Sidewalls with PG Knockouts (metric available)

| Ordering Information   | Height mm (in)  | Polystyrene |             |             |          | Polycarbonate |             |             |          |
|------------------------|-----------------|-------------|-------------|-------------|----------|---------------|-------------|-------------|----------|
|                        |                 | Cat. No.    | Type        | Cover Color | Std. Pk. | Cat. No.      | Type        | Cover Color | Std. Pk. |
| Enclosure - low cover  | 57 mm (2.24 in) | 115-409     | PS 1309-6   | gray        | 3        | 125-409       | PC 1309-6   | gray        | 3        |
| Enclosure - high cover | 81 mm (3.19 in) | 115-909     | PS 1309-8   | gray        | 3        | 125-909       | PC 1309-8   | gray        | 3        |
| Enclosure - low cover  | 57 mm (2.24 in) | 116-009     | PS 1309-6-t | trans.      | 3        | 135-009       | PC 1309-6-t | trans.      | 3        |
| Enclosure - high cover | 81 mm (3.19 in) | 116-509     | PS 1309-8-t | trans.      | 3        | 135-509       | PC 1309-8-t | trans.      | 3        |

## RK Enclosures with Terminal Blocks

| Ordering Information                | Height          | Cat. No. | Type   | Cover Color | Std. Pk. |
|-------------------------------------|-----------------|----------|--------|-------------|----------|
| Enclosure - 15 pole/12 AWG Terminal | 57 mm (2.24 in) | 612-404  | RK1309 | gray        | 3        |
| Enclosure - DIN Rail only (TS15)    | 57 mm (2.24 in) | 612-904  | RK1309 | gray        | 3        |

## Accessories

| Ordering Information | Cat. No. | Type      | Std. Pk. |
|----------------------|----------|-----------|----------|
| Mounting Plate       | 195-009  | MP1309    | 1        |
| DIN Rail TS35-106mm  | Z-658    | TS 35/106 | 1        |
| DIN Rail TS15-111mm  | Z-632    | TS 15/111 | 1        |
| Hinge Kit Set        | 190-002  | HK1       | 1        |
| Mounting Tab Kit     | 194-001  | MT1       | 1        |

Please refer to pages 106-113 for additional accessories and detailed information.

<sup>①</sup> Clear transparent lids available upon request

# TK 1313 – Polystyrene and Polycarbonate – 130x130mm (5.12x5.12in.)

## Standard Features

- **Protection Level:** IP66 (NEMA 4X)
- **Technical:** Smooth or Knockout Sidewalls  
Gray or Tinted Transparent Cover <sup>①</sup>  
Multiple Enclosure Mounting Options
- **Enclosure Material:** Polystyrene or Polycarbonate
- **Gasket Material:** Polyurethane
- **Color:** Light Gray
- **Temperature Range:** Polystyrene  
-40°C to 70°C (-40°F to 158°F)  
Polycarbonate  
-35°C to 120°C (-31°F to 248°F)
- **Accessories:** See section below



## Smooth Sidewalls

### Polystyrene

### Polycarbonate

| Ordering Information     | Height mm (in)  | Cat. No. | Type          | Cover Color | Std. Pk. | Cat. No. | Type          | Cover Color | Std. Pk. |
|--------------------------|-----------------|----------|---------------|-------------|----------|----------|---------------|-------------|----------|
| ☐ Enclosure - low cover  | 75 mm (2.95 in) | 110-405  | PS 1313-7-o   | gray        | 2        | 120-405  | PC 1313-7-o   | gray        | 2        |
| ☐ Enclosure - high cover | 99 mm (3.90 in) | 110-905  | PS 1313-10-o  | gray        | 2        | 120-905  | PC 1313-10-o  | gray        | 2        |
| ☐ Enclosure - low cover  | 75 mm (2.95 in) | 111-005  | PS 1313-7-to  | trans.      | 2        | 130-005  | PC 1313-7-to  | trans.      | 2        |
| ☐ Enclosure - high cover | 99 mm (3.90 in) | 111-505  | PS 1313-10-to | trans.      | 2        | 130-505  | PC 1313-10-to | trans.      | 2        |

## Sidewalls with PG Knockouts (metric available)

### Polystyrene

### Polycarbonate

| Ordering Information     | Height mm (in)  | Cat. No. | Type         | Cover Color | Std. Pk. | Cat. No. | Type         | Cover Color | Std. Pk. |
|--------------------------|-----------------|----------|--------------|-------------|----------|----------|--------------|-------------|----------|
| ☐ Enclosure - low cover  | 75 mm (2.95 in) | 115-405  | PS 1313-7    | gray        | 2        | 125-405  | PC 1313-7    | gray        | 2        |
| ☐ Enclosure - high cover | 99 mm (3.90 in) | 115-905  | PS 1313-10   | gray        | 2        | 125-905  | PC 1313-10   | gray        | 2        |
| ☐ Enclosure - low cover  | 75 mm (2.95 in) | 116-005  | PS 1313-7-t  | trans.      | 2        | 135-005  | PC 1313-7-t  | trans.      | 2        |
| ☐ Enclosure - high cover | 99 mm (3.90 in) | 116-505  | PS 1313-10-t | trans.      | 2        | 135-505  | PC 1313-10-t | trans.      | 2        |

## RK Enclosures with Terminal Blocks

| Ordering Information                | Height          | Cat. No. | Type   | Cover Color | Std. Pk. |
|-------------------------------------|-----------------|----------|--------|-------------|----------|
| Enclosure - 15 pole/10 AWG Terminal | 75 mm (2.95 in) | 613-404  | RK1313 | gray        | 2        |
| Enclosure - DIN Rail only (TS35)    | 75 mm (2.95 in) | 613-906  | RK1313 | gray        | 2        |

## Accessories

| Ordering Information | Cat. No. | Type      | Std. Pk. |
|----------------------|----------|-----------|----------|
| Mounting Plate       | 195-005  | MP1313    | 1        |
| DIN Rail TS35-106mm  | Z-658    | TS 35/106 | 1        |
| DIN Rail TS15-111mm  | Z-632    | TS 15/111 | 1        |
| Hinge Kit Set        | 190-002  | HK1       | 1        |
| Mounting Tab Kit     | 194-001  | MT1       | 1        |

Please refer to pages 106-113 for additional accessories and detailed information.

<sup>①</sup> Clear transparent lids available upon request

# TK 1809 – Polystyrene and Polycarbonate – 180x94mm (7.09x3.70in.)

## Standard Features

- **Protection Level:** IP66 (NEMA 4X)
- **Technical:** Smooth or Knockout Sidewalls  
Gray or Tinted Transparent Cover <sup>①</sup>  
Multiple Enclosure Mounting Options
- **Enclosure Material:** Polystyrene or Polycarbonate
- **Gasket Material:** Polyurethane
- **Color:** Light Gray
- **Temperature Range:** Polystyrene  
-40°C to 70°C (-40°F to 158°F)  
Polycarbonate  
-35°C to 120°C (-31°F to 248°F)
- **Accessories:** See section below



## Smooth Sidewalls

| Ordering Information   | Height mm (in)  | Polystyrene |              |             |          | Polycarbonate |              |             |          |
|------------------------|-----------------|-------------|--------------|-------------|----------|---------------|--------------|-------------|----------|
|                        |                 | Cat. No.    | Type         | Cover Color | Std. Pk. | Cat. No.      | Type         | Cover Color | Std. Pk. |
| Enclosure - low cover  | 57 mm (2.24 in) | 110-410     | PS 1809-6-o  | gray        | 2        | 120-410       | PC 1809-6-o  | gray        | 2        |
| Enclosure - high cover | 81 mm (3.19 in) | 110-910     | PS 1809-8-o  | gray        | 2        | 120-910       | PC 1809-8-o  | gray        | 2        |
| Enclosure - low cover  | 57 mm (2.24 in) | 111-010     | PS 1809-6-to | trans.      | 2        | 130-010       | PC 1809-6-to | trans.      | 2        |
| Enclosure - high cover | 81 mm (3.19 in) | 111-510     | PS 1809-8-to | trans.      | 2        | 130-510       | PC 1809-8-to | trans.      | 2        |

## Sidewalls with PG Knockouts (metric available)

| Ordering Information   | Height mm (in)  | Polystyrene |             |             |          | Polycarbonate |             |             |          |
|------------------------|-----------------|-------------|-------------|-------------|----------|---------------|-------------|-------------|----------|
|                        |                 | Cat. No.    | Type        | Cover Color | Std. Pk. | Cat. No.      | Type        | Cover Color | Std. Pk. |
| Enclosure - low cover  | 57 mm (2.24 in) | 115-410     | PS 1809-6   | gray        | 2        | 125-410       | PC 1809-6   | gray        | 2        |
| Enclosure - high cover | 81 mm (3.19 in) | 115-910     | PS 1809-8   | gray        | 2        | 125-910       | PC 1809-8   | gray        | 2        |
| Enclosure - low cover  | 57 mm (2.24 in) | 116-010     | PS 1809-6-t | trans.      | 2        | 135-010       | PC 1809-6-t | trans.      | 2        |
| Enclosure - high cover | 81 mm (3.19 in) | 116-510     | PS 1809-8-t | trans.      | 2        | 135-510       | PC 1809-8-t | trans.      | 2        |

## RK Enclosures with Terminal Blocks

| Ordering Information                | Height          | Cat. No. | Type   | Cover Color | Std. Pk. |
|-------------------------------------|-----------------|----------|--------|-------------|----------|
| Enclosure - 22 pole/12 AWG Terminal | 57 mm (2.24 in) | 614-404  | RK1809 | gray        | 2        |
| Enclosure - DIN Rail only (TS15)    | 57 mm (2.24 in) | 614-906  | RK1809 | gray        | 2        |

## Accessories

| Ordering Information | Cat. No. | Type      | Std. Pk. |
|----------------------|----------|-----------|----------|
| Mounting Plate       | 195-010  | MP1809    | 1        |
| DIN Rail TS35-144mm  | Z-655    | TS 35/144 | 1        |
| DIN Rail TS15-154mm  | Z-636    | TS 15/154 | 1        |
| Hinge Kit Set        | 190-002  | HK1       | 1        |
| Mounting Tab Kit     | 194-001  | MT1       | 1        |

Please refer to pages 106-113 for additional accessories and detailed information.

<sup>①</sup> Clear transparent lids available upon request

## Standard Features

- **Protection Level:** IP66 (NEMA 4X)
- **Technical:** Smooth or Knockout Sidewalls  
Gray or Tinted Transparent Cover ①  
Multiple Enclosure Mounting Options
- **Enclosure Material:** Polystyrene or Polycarbonate
- **Gasket Material:** Polyurethane
- **Color:** Light Gray
- **Temperature Range:** Polystyrene  
-40°C to 70°C (-40°F to 158°F)  
Polycarbonate  
-35°C to 120°C (-31°F to 248°F)
- **Accessories:** See section below



## Smooth Sidewalls

| Ordering Information        | Height mm (in)   | Polystyrene |               |             |          | Polycarbonate |               |             |          |
|-----------------------------|------------------|-------------|---------------|-------------|----------|---------------|---------------|-------------|----------|
|                             |                  | Cat. No.    | Type          | Cover Color | Std. Pk. | Cat. No.      | Type          | Cover Color | Std. Pk. |
| ☐ Enclosure - low cover     | 90 mm (3.54 in)  | 110-406     | PS 1811-9-o   | gray        | 2        | 120-406       | PC 1811-9-o   | gray        | 2        |
| ☐ Enclosure - high cover    | 111 mm (4.37 in) | 110-906     | PS 1811-11-o  | gray        | 2        | 120-906       | PC 1811-11-o  | gray        | 2        |
| ☐ Enclosure - top hat cover | 165 mm (6.50 in) | 109-406     | PS 1811-16-o  | gray        | 2        | 121-406       | PC 1811-16-o  | gray        | 2        |
| ☐ Enclosure - low cover     | 90 mm (3.54 in)  | 111-006     | PS 1811-9-to  | trans.      | 2        | 130-006       | PC 1811-9-to  | trans.      | 2        |
| ☐ Enclosure - high cover    | 111 mm (4.37 in) | 111-506     | PS 1811-11-to | trans.      | 2        | 130-506       | PC 1811-11-to | trans.      | 2        |
| ☐ Enclosure - top hat cover | 165 mm (6.50 in) | 112-006     | PS 1811-16-to | trans.      | 2        | 131-006       | PC 1811-16-to | trans.      | 2        |

## Sidewalls with PG Knockouts (metric available)

| Ordering Information        | Height mm (in)   | Polystyrene |              |             |          | Polycarbonate |              |             |          |
|-----------------------------|------------------|-------------|--------------|-------------|----------|---------------|--------------|-------------|----------|
|                             |                  | Cat. No.    | Type         | Cover Color | Std. Pk. | Cat. No.      | Type         | Cover Color | Std. Pk. |
| ☐ Enclosure - low cover     | 90 mm (3.54 in)  | 115-406     | PS 1811-9    | gray        | 2        | 125-406       | PC 1811-9    | gray        | 2        |
| ☐ Enclosure - high cover    | 111 mm (4.37 in) | 115-906     | PS 1811-11   | gray        | 2        | 125-906       | PC 1811-11   | gray        | 2        |
| ☐ Enclosure - top hat cover | 165 mm (6.50 in) | 114-406     | PS 1811-16   | gray        | 2        | 126-406       | PC 1811-16   | gray        | 2        |
| ☐ Enclosure - low cover     | 90 mm (3.54 in)  | 116-006     | PS 1811-9-t  | trans.      | 2        | 135-006       | PC 1811-9-t  | trans.      | 2        |
| ☐ Enclosure - high cover    | 111 mm (4.37 in) | 116-506     | PS 1811-11-t | trans.      | 2        | 135-506       | PC 1811-11-t | trans.      | 2        |
| ☐ Enclosure - top hat cover | 165 mm (6.50 in) | 117-006     | PS 1811-16-t | trans.      | 2        | 136-006       | PC 1811-16-t | trans.      | 2        |

## RK Enclosures with Terminal Blocks

| Ordering Information                | Height          | Cat. No. | Type   | Cover Color | Std. Pk. |
|-------------------------------------|-----------------|----------|--------|-------------|----------|
| Enclosure - 21 pole/10 AWG Terminal | 90 mm (3.54 in) | 615-404  | RK1811 | gray        | 2        |
| Enclosure - DIN Rail only (TS35)    | 90 mm (3.54 in) | 615-912  | RK1811 | gray        | 2        |

## Accessories

| Ordering Information | Cat. No. | Type      | Std. Pk. |
|----------------------|----------|-----------|----------|
| Mounting Plate       | 195-006  | MP1811    | 1        |
| DIN Rail TS35-144mm  | Z-655    | TS 35/144 | 1        |
| Hinge Kit Set        | 190-005  | HK2       | 1        |
| Mounting Tab Kit     | 194-001  | MT1       | 1        |

Please refer to pages 106-113 for additional accessories and detailed information.

① Clear transparent lids available upon request

# TK 1818 – Polystyrene and Polycarbonate – 182x180mm (7.17x7.09in.)

## Standard Features

- **Protection Level:** IP66 (NEMA 4X)
- **Technical:** Smooth or Knockout Sidewalls  
Gray or Tinted Transparent Cover <sup>①</sup>  
Multiple Enclosure Mounting Options
- **Enclosure Material:** Polystyrene or Polycarbonate
- **Gasket Material:** Polyurethane
- **Color:** Light Gray
- **Temperature Range:** Polystyrene  
-40°C to 70°C (-40°F to 158°F)  
Polycarbonate  
-35°C to 120°C (-31°F to 248°F)
- **Accessories:** See section below



## Smooth Sidewalls

| Ordering Information      | Height mm (in)   | Polystyrene |               |             |          | Polycarbonate |               |             |          |
|---------------------------|------------------|-------------|---------------|-------------|----------|---------------|---------------|-------------|----------|
|                           |                  | Cat. No.    | Type          | Cover Color | Std. Pk. | Cat. No.      | Type          | Cover Color | Std. Pk. |
| Enclosure - low cover     | 90 mm (3.54 in)  | 110-407     | PS 1818-9-o   | gray        | 2        | 120-407       | PC 1818-9-o   | gray        | 2        |
| Enclosure - high cover    | 111 mm (4.37 in) | 110-907     | PS 1818-11-o  | gray        | 2        | 120-907       | PC 1818-11-o  | gray        | 2        |
| Enclosure - top hat cover | 165 mm (6.50 in) | 109-407     | PS 1818-16-o  | gray        | 1        | 121-407       | PC 1818-16-o  | gray        | 1        |
| Enclosure - low cover     | 90 mm (3.54 in)  | 111-007     | PS 1818-9-to  | trans.      | 2        | 130-007       | PC 1818-9-to  | trans.      | 2        |
| Enclosure - high cover    | 111 mm (4.37 in) | 111-507     | PS 1818-11-to | trans.      | 2        | 130-507       | PC 1818-11-to | trans.      | 2        |
| Enclosure - top hat cover | 165 mm (6.50 in) | 112-007     | PS 1818-16-to | trans.      | 1        | 131-007       | PC 1818-16-to | trans.      | 1        |

## Sidewalls with PG Knockouts (metric available)

| Ordering Information      | Height mm (in)   | Polystyrene |              |             |          | Polycarbonate |              |             |          |
|---------------------------|------------------|-------------|--------------|-------------|----------|---------------|--------------|-------------|----------|
|                           |                  | Cat. No.    | Type         | Cover Color | Std. Pk. | Cat. No.      | Type         | Cover Color | Std. Pk. |
| Enclosure - low cover     | 90 mm (3.54 in)  | 115-407     | PS 1818-9    | gray        | 2        | 125-407       | PC 1818-9    | gray        | 2        |
| Enclosure - high cover    | 111 mm (4.37 in) | 115-907     | PS 1818-11   | gray        | 2        | 125-907       | PC 1818-11   | gray        | 2        |
| Enclosure - top hat cover | 165 mm (6.50 in) | 114-407     | PS 1818-16   | gray        | 1        | 126-407       | PC 1818-16   | gray        | 1        |
| Enclosure - low cover     | 90 mm (3.54 in)  | 116-007     | PS 1818-9-t  | trans.      | 2        | 135-007       | PC 1818-9-t  | trans.      | 2        |
| Enclosure - high cover    | 111 mm (4.37 in) | 116-507     | PS 1818-11-t | trans.      | 2        | 135-507       | PC 1818-11-t | trans.      | 2        |
| Enclosure - top hat cover | 165 mm (6.50 in) | 117-007     | PS 1818-16-t | trans.      | 1        | 136-007       | PC 1818-16-t | trans.      | 1        |

## RK Enclosures with Terminal Blocks

| Ordering Information                | Height          | Cat. No. | Type   | Cover Color | Std. Pk. |
|-------------------------------------|-----------------|----------|--------|-------------|----------|
| Enclosure - 21 pole/10 AWG Terminal | 90 mm (3.54 in) | 616-404  | RK1818 | gray        | 2        |
| Enclosure - DIN Rail only (TS35)    | 90 mm (3.54 in) | 616-912  | RK1818 | gray        | 2        |

## Accessories

| Ordering Information | Cat. No. | Type      | Std. Pk. |
|----------------------|----------|-----------|----------|
| Mounting Plate       | 195-007  | MP1818    | 1        |
| DIN Rail TS35-144mm  | Z-655    | TS 35/144 | 1        |
| Hinge Kit Set        | 190-005  | HK2       | 1        |
| Mounting Tab Kit     | 194-001  | MT1       | 1        |


Please refer to pages 106-113 for additional accessories and detailed information.

<sup>①</sup> Clear transparent lids available upon request

# TK 2518f – Polystyrene and Polycarbonate – 254x180mm (10.0x7.09in.)

## Standard Features

- **Protection Level:** IP66 (NEMA 4X)
- **Technical:** Smooth or Knockout Sidewalls  
Gray or Tinted Transparent Cover <sup>①</sup>  
Multiple Enclosure Mounting Options
- **Enclosure Material:** Polystyrene or Polycarbonate
- **Gasket Material:** Polyurethane
- **Color:** Light Gray
- **Temperature Range:** Polystyrene  
-40°C to 70°C (-40°F to 158°F)  
Polycarbonate  
-35°C to 120°C (-31°F to 248°F)
- **Accessories:** See section below



## Smooth Sidewalls

| Ordering Information      | Height mm (in)   | Polystyrene |                |             |          | Polycarbonate |                |             |          |
|---------------------------|------------------|-------------|----------------|-------------|----------|---------------|----------------|-------------|----------|
|                           |                  | Cat. No.    | Type           | Cover Color | Std. Pk. | Cat. No.      | Type           | Cover Color | Std. Pk. |
| Enclosure - low cover     | 63 mm (2.48 in)  | 110-411     | PS 2518-6f-o   | gray        | 1        | 120-411       | PC 2518-6f-o   | gray        | 1        |
| Enclosure - high cover    | 84 mm (3.31 in)  | 110-911     | PS 2518-8f-o   | gray        | 1        | 120-911       | PC 2518-8f-o   | gray        | 1        |
| Enclosure - top hat cover | 137 mm (5.39 in) | 109-411     | PS 2518-14f-o  | gray        | 1        | 121-411       | PC 2518-14f-o  | gray        | 1        |
| Enclosure - low cover     | 63 mm (2.48 in)  | 111-011     | PS 2518-6f-to  | trans.      | 1        | 130-011       | PC 2518-6f-to  | trans.      | 1        |
| Enclosure - high cover    | 84 mm (3.31 in)  | 111-511     | PS 2518-8f-to  | trans.      | 1        | 130-511       | PC 2518-8f-to  | trans.      | 1        |
| Enclosure - top hat cover | 137 mm (5.39 in) | 112-011     | PS 2518-14f-to | trans.      | 1        | 131-011       | PC 2518-14f-to | trans.      | 1        |

## Sidewalls with Metric Knockouts

| Ordering Information      | Height mm (in)   | Polystyrene |               |             |          | Polycarbonate |               |             |          |
|---------------------------|------------------|-------------|---------------|-------------|----------|---------------|---------------|-------------|----------|
|                           |                  | Cat. No.    | Type          | Cover Color | Std. Pk. | Cat. No.      | Type          | Cover Color | Std. Pk. |
| Enclosure - low cover     | 63 mm (2.48 in)  | 105-411     | PS 2518-6f    | gray        | 1        | 127-411       | PC 2518-6f    | gray        | 1        |
| Enclosure - high cover    | 84 mm (3.31 in)  | 105-911     | PS 2518-8f    | gray        | 1        | 127-911       | PC 2518-8f    | gray        | 1        |
| Enclosure - top hat cover | 137 mm (5.39 in) | 104-411     | PS 2518-14f   | gray        | 1        | 128-411       | PC 2518-14f   | gray        | 1        |
| Enclosure - low cover     | 63 mm (2.48 in)  | 106-011     | PS 2518-6f-t  | trans.      | 1        | 137-011       | PC 2518-6f-t  | trans.      | 1        |
| Enclosure - high cover    | 84 mm (3.31 in)  | 106-511     | PS 2518-8f-t  | trans.      | 1        | 137-511       | PC 2518-8f-t  | trans.      | 1        |
| Enclosure - top hat cover | 137 mm (5.39 in) | 107-011     | PS 2518-14f-t | trans.      | 1        | 138-011       | PC 2518-14f-t | trans.      | 1        |

## Accessories

| Ordering Information | Cat. No. | Type      | Std. Pk. |
|----------------------|----------|-----------|----------|
| Mounting Plate       | 195-008  | MP2518    | 1        |
| DIN Rail TS35-216mm  | Z-652    | TS 35/216 | 1        |
| Hinge Kit Set        | 190-005  | HK2       | 1        |
| Mounting Tab Kit     | 194-001  | MT1       | 1        |

Please refer to pages 106-113 for additional accessories and detailed information.

<sup>①</sup> Clear transparent lids available upon request

## Standard Features

- **Protection Level:** IP66 (NEMA 4X)
- **Technical:** Smooth or Knockout Sidewalls  
Gray or Tinted Transparent Cover ①  
Multiple Enclosure Mounting Options
- **Enclosure Material:** Polystyrene or Polycarbonate
- **Gasket Material:** Polyurethane
- **Color:** Light Gray
- **Temperature Range:** Polystyrene  
-40°C to 70°C (-40°F to 158°F)  
Polycarbonate  
-35°C to 120°C (-31°F to 248°F)
- **Accessories:** See section below



## Smooth Sidewalls

| Ordering Information        | Height mm (in)   | Polystyrene |               |             |          | Polycarbonate |               |             |          |
|-----------------------------|------------------|-------------|---------------|-------------|----------|---------------|---------------|-------------|----------|
|                             |                  | Cat. No.    | Type          | Cover Color | Std. Pk. | Cat. No.      | Type          | Cover Color | Std. Pk. |
| ☐ Enclosure - low cover     | 90 mm (3.54 in)  | 110-408     | PS 2518-9-o   | gray        | 1        | 120-408       | PC 2518-9-o   | gray        | 1        |
| ☐ Enclosure - high cover    | 111 mm (4.37 in) | 110-908     | PS 2518-11-o  | gray        | 1        | 120-908       | PC 2518-11-o  | gray        | 1        |
| ☐ Enclosure - top hat cover | 165 mm (6.50 in) | 109-408     | PS 2518-16-o  | gray        | 1        | 121-408       | PC 2518-16-o  | gray        | 1        |
| ☐ Enclosure - low cover     | 90 mm (3.54 in)  | 111-008     | PS 2518-9-to  | trans.      | 1        | 130-008       | PC 2518-9-to  | trans.      | 1        |
| ☐ Enclosure - high cover    | 111 mm (4.37 in) | 111-508     | PS 2518-11-to | trans.      | 1        | 130-508       | PC 2518-11-to | trans.      | 1        |
| ☐ Enclosure - top hat cover | 165 mm (6.50 in) | 112-008     | PS 2518-16-to | trans.      | 1        | 131-008       | PC 2518-16-to | trans.      | 1        |

## Sidewalls with PG Knockouts (metric available)

| Ordering Information        | Height mm (in)   | Polystyrene |              |             |          | Polycarbonate |              |             |          |
|-----------------------------|------------------|-------------|--------------|-------------|----------|---------------|--------------|-------------|----------|
|                             |                  | Cat. No.    | Type         | Cover Color | Std. Pk. | Cat. No.      | Type         | Cover Color | Std. Pk. |
| ☐ Enclosure - low cover     | 90 mm (3.54 in)  | 115-408     | PS 2518-9    | gray        | 1        | 125-408       | PC 2518-9    | gray        | 1        |
| ☐ Enclosure - high cover    | 111 mm (4.37 in) | 115-908     | PS 2518-11   | gray        | 1        | 125-908       | PC 2518-11   | gray        | 1        |
| ☐ Enclosure - top hat cover | 165 mm (6.50 in) | 114-408     | PS 2518-16   | gray        | 1        | 126-408       | PC 2518-16   | gray        | 1        |
| ☐ Enclosure - low cover     | 90 mm (3.54 in)  | 116-008     | PS 2518-9-t  | trans.      | 1        | 135-008       | PC 2518-9-t  | trans.      | 1        |
| ☐ Enclosure - high cover    | 111 mm (4.37 in) | 116-508     | PS 2518-11-t | trans.      | 1        | 135-508       | PC 2518-11-t | trans.      | 1        |
| ☐ Enclosure - top hat cover | 165 mm (6.50 in) | 117-008     | PS 2518-16-t | trans.      | 1        | 136-008       | PC 2518-16-t | trans.      | 1        |

## RK Enclosures with Terminal Blocks

| Ordering Information                | Height          | Cat. No. | Type   | Cover Color | Std. Pk. |
|-------------------------------------|-----------------|----------|--------|-------------|----------|
| Enclosure - 32 pole/10 AWG Terminal | 90 mm (3.54 in) | 625-404  | RK2518 | gray        | 1        |
| Enclosure - DIN Rail only (TS35)    | 90 mm (3.54 in) | 625-916  | RK2518 | gray        | 1        |

## Accessories

| Ordering Information | Cat. No. | Type      | Std. Pk. |
|----------------------|----------|-----------|----------|
| Mounting Plate       | 195-008  | MP2518    | 1        |
| DIN Rail TS35-216mm  | Z-652    | TS 35/216 | 1        |
| Hinge Kit Set        | 190-005  | HK2       | 1        |
| Mounting Tab Kit     | 194-001  | MT1       | 1        |

Please refer to pages 106-113 for additional accessories and detailed information.

① Clear transparent lids available upon request

# TK 3625 – Polystyrene and Polycarbonate – 360x254mm (14.2x10.0in.)

## Standard Features

- **Protection Level:** IP66 (NEMA 4X)
- **Technical:** Smooth or Knockout Sidewalls  
Gray or Tinted Transparent Cover <sup>①</sup>  
Multiple Enclosure Mounting Options
- **Enclosure Material:** Polystyrene or Polycarbonate
- **Gasket Material:** Polyurethane
- **Color:** Light Gray
- **Temperature Range:** Polystyrene  
-40°C to 70°C (-40°F to 158°F)  
Polycarbonate  
-35°C to 120°C (-31°F to 248°F)
- **Accessories:** See section below



## Smooth Sidewalls

### Polystyrene

### Polycarbonate

| Ordering Information        | Height mm (in)   | Cat. No. | Type          | Cover Color | Std. Pk. | Cat. No. | Type          | Cover Color | Std. Pk. |
|-----------------------------|------------------|----------|---------------|-------------|----------|----------|---------------|-------------|----------|
| ☐ Enclosure - low cover     | 111 mm (4.37 in) | 110-412  | PS 3625-11-o  | gray        | 1        | 120-412  | PC 3625-11-o  | gray        | 1        |
| ☐ Enclosure - high cover    | 165 mm (6.50 in) | 110-912  | PS 3625-16-o  | gray        | 1        | 120-912  | PC 3625-16-o  | gray        | 1        |
| ☐ Enclosure - top hat cover | 215 mm (8.46 in) | 109-412  | PS 3625-21-o  | gray        | 1        | 121-412  | PC 3625-21-o  | gray        | 1        |
| ☐ Enclosure - low cover     | 111 mm (4.37 in) | 111-012  | PS 3625-11-to | trans.      | 1        | 130-012  | PC 3625-11-to | trans.      | 1        |
| ☐ Enclosure - high cover    | 165 mm (6.50 in) | 111-512  | PS 3625-16-to | trans.      | 1        | 130-512  | PC 3625-16-to | trans.      | 1        |
| ☐ Enclosure - top hat cover | 215 mm (8.46 in) | 112-012  | PS 3625-21-to | trans.      | 1        | 131-012  | PC 3625-21-to | trans.      | 1        |

## Sidewalls with PG Knockouts (metric available)

### Polystyrene

### Polycarbonate

| Ordering Information        | Height mm (in)   | Cat. No. | Type         | Cover Color | Std. Pk. | Cat. No. | Type         | Cover Color | Std. Pk. |
|-----------------------------|------------------|----------|--------------|-------------|----------|----------|--------------|-------------|----------|
| ☐ Enclosure - low cover     | 111 mm (4.37 in) | 115-412  | PS 3625-11   | gray        | 1        | 125-412  | PC 3625-11   | gray        | 1        |
| ☐ Enclosure - high cover    | 165 mm (6.50 in) | 115-912  | PS 3625-16   | gray        | 1        | 125-912  | PC 3625-16   | gray        | 1        |
| ☐ Enclosure - top hat cover | 215 mm (8.46 in) | 114-412  | PS 3625-21   | gray        | 1        | 126-412  | PC 3625-21   | gray        | 1        |
| ☐ Enclosure - low cover     | 111 mm (4.37 in) | 116-012  | PS 3625-11-t | trans.      | 1        | 135-012  | PC 3625-11-t | trans.      | 1        |
| ☐ Enclosure - high cover    | 165 mm (6.50 in) | 116-512  | PS 3625-16-t | trans.      | 1        | 135-512  | PC 3625-16-t | trans.      | 1        |
| ☐ Enclosure - top hat cover | 215 mm (8.46 in) | 117-012  | PS 3625-21-t | trans.      | 1        | 136-012  | PC 3625-21-t | trans.      | 1        |

## RK Enclosures with Terminal Blocks

| Ordering Information                  | Height           | Cat. No. | Type   | Cover Color | Std. Pk. |
|---------------------------------------|------------------|----------|--------|-------------|----------|
| Enclosure - 100 pole/10 AWG Terminal  | 111 mm (4.37 in) | 626-404  | RK3625 | gray        | 1        |
| Enclosure - DIN Rail only (2x) (TS35) | 111 mm (4.37 in) | 626-922  | RK3625 | gray        | 1        |

## Accessories

| Ordering Information | Cat. No. | Type       | Std. Pk. |
|----------------------|----------|------------|----------|
| Mounting Plate       | 195-012  | MP3625     | 1        |
| DIN Rail TS35-336mm  | Z-663    | TS 35/ 336 | 1        |
| Hinge Kit Set        | 190-005  | HK2        | 1        |
| Mounting Tab Kit     | 194-001  | MT1        | 1        |

Please refer to pages 106-113 for additional accessories and detailed information.

<sup>①</sup> Clear transparent lids available upon request