


FEED-THROUGH FLAT BASE
EUROSTRIPS
35 or 32mm DIN Rail

For wire-to-wire connections in HVAC, appliance, equipment, power distribution and other industrial applications with strict budget and space requirements. Easy to use double row terminal strips are a cost-effective alternative to barrier strips or other types of terminal blocks. Simply strip the wire, insert and tighten the screw. Eurostrips feature tubular screw clamps, with wire protectors, and recessed metal parts for finger protection. The wire protectors include an integral wire stop in the center of the terminal. The stainless steel wire protectors exhibit excellent memory and the wire stop insures the most effective connection.

Eurostrips described on this and the following page are available with a flat base for minimum clearance applications. They can be panel mounted or left to free float. Offered in easy to cut standard 12 pole strips, they can also be ordered precut with the required number of poles.


- Tubular screw clamp
- Panel mount or free float
- Housing material: polyamide 6.6
- Color: opaque white
- Marking plates or factory imprinted application

TS1.5



Flat base with wire protector

TS2.5




Flat base with wire protector

Pole Spacing	8 mm		
Mounting Hole Diameter	2.8 mm		
Stripping Length	5 mm		
Approvals			
Wire Range	1.5 mm ²	22-12 AWG	22-16 AWG
Voltage Rating	380 V	300 V	300 V
Current Rating	18 A	20 A	15 A
Torque	0.5 Nm	4.4 lbf/in	

Pole Spacing	10 mm		
Mounting Hole Diameter	3.5 mm		
Stripping Length	6 mm		
Approvals			
Wire Range	2.5 mm ²	22-10 AWG	18-12 AWG
Voltage Rating	380 V	300 V	300 V
Current Rating	26 A	30 A	30 A
Torque	0.8 Nm	7.0 lbf/in	


No. of Poles	Cat. No.	Std. Pk.	Length
2	40.002	100	13.6 mm
3	40.003	100	21.5 mm
4	40.004	100	29.5 mm
5	40.005	100	37.4 mm
6	40.006	50	45.5 mm
7	40.007	50	53.5 mm
8	40.008	50	61.3 mm
9	40.009	50	69.2 mm
10	40.010	50	77.2 mm
11	40.011	50	85.1 mm
12	40.012	50	93.0 mm

Cat. No.	Std. Pk.	Length
40.202	100	17.0 mm
40.203	100	27.0 mm
40.204	100	37.0 mm
40.205	100	47.0 mm
40.206	50	57.0 mm
40.207	50	67.0 mm
40.208	50	77.0 mm
40.209	50	87.0 mm
40.210	50	97.0 mm
40.211	50	107.0 mm
40.212	50	117.0 mm



Dimensions mm (in.)


A=8.0 (.315)	H=Ø3.0 (.118)
B=M2.5 x 4.3	I=2.5 (.099)
C=5.6 (.221)	J=7.5 (.296)
D=2.4 (.095)	K=6.7 (.264)
E=Ø2.8 (.110)	M=13.7 (.540)
F=Ø5.35 (.211)	N=18.2 (.716)
G=8.0 (.315)	



Dimensions mm (in.)

A=10.0 (.394)	H=Ø3.6 (.142)
B=M3 x 5.8	I=3.0 (.118)
C=6.4 (.252)	J=9.5 (.374)
D=3.5 (.138)	K=8.0 (.315)
E=Ø3.5 (.137)	M=15.5 (.611)
F=Ø5.7 (.225)	N=21.8 (.858)
G=10.0 (.394)	

TS6



Flat base with wire protector

12 mm

4.2 mm

7 mm



6 mm²

20-8 AWG

18-10 AWG

380 V

300 V

300 V

44 A


40 A

40 A

0.8 Nm

7.0 lbf/in

Cat. No.	Std. Pk.	Length
40.402	100	20.0 mm
40.403	100	32.0 mm
40.404	100	44.0 mm
40.405	100	56.0 mm
40.406	50	68.0 mm
40.407	50	80.0 mm
40.408	50	92.0 mm
40.409	50	104.0 mm
40.410	25	116.0 mm
40.411	25	128.0 mm
40.412	25	140.0 mm



Dimensions mm (in.)

A=12.0 (.472)	H=Ø4.2 (.165)
B=M3.5 x 7	I=4.3 (.169)
C=7.6 (.299)	J=9.5 (.374)
D=4.3 (.169)	K=9.0 (.354)
E=Ø4.2 (.165)	M=17.7 (.697)
F=Ø6.8 (.268)	N=23.0 (.906)
G=12.0 (.472)	