

## Specification Sheet

Part Number: 126-03100



1-Pc Cable Tie/Arrowhead Mount with Seal, 6.3" Long, 50lb Tensile, PA66HS, Green, 500/bag

**Article Number** 126-03100

**Type** T50SOSSFT6.5E-MDL

**Color** Green (GN)

**Features & Benefits** This tie has an arrowhead design of fixing which offers a positive, low push-in force and a high pull-out force. When combined with the optional foam rubber seal it offers additional protection against the ingress of moisture or dirt.

**Quantity Per** bag

**Product Description** Arrowhead Push Ties with rubber seal secure fast and easy, while providing a special rubber seal to minimize water, dirt, or dust from getting through the mounting hole. The anchor adjusts for variations in panel thicknesses which insures a secure fixing at all times.

|  |   |
|--|---|
| <b>Short Description</b>                   | 1-Pc Cable Tie/Arrowhead Mount with Seal, 6.3" Long, 50lb Tensile, PA66HS, Green, 500/bag |
| <b>Global Part Name</b>                    | T50SOSSFT6.5E-MDL-PA66HS-GN   |
| <b>Minimum Tensile Strength (Imperial)</b> | 50.0  |
| <b>Minimum Tensile Strength (Metric)</b>   | 225   |
| <b>Length L (Imperial)</b>                 | 6.3   |
| <b>Length L (Metric)</b>                   | 158.8   |
| <b>Fixation Method</b>                     | Arrowhead   |
| <b>Identification Plate Position</b>       | none  |
| <b>Releasable Closure</b>                  | No  |
| <b>Tie Closure</b>                         | plastic pawl  |
| <b>Variant</b>                             | Outside Serrated  |
| <b>Width W (Imperial)</b>                  | 0.18  |
| <b>Width W (Metric)</b>                    | 4.6   |
| <b>Bundle Diameter Min (Imperial)</b>      | 0.06  |
| <b>Bundle Diameter Min (Metric)</b>        | 1.5   |

|  |              |
|--|--------------|
| <b>Bundle Diameter Max (Imperial)</b>          | 1.18         |
| <b>Bundle Diameter Max (Metric)</b>            | 30.0         |
| <b>Thickness T (Imperial)</b>                  | 0.05         |
| <b>Thickness T (Metric)</b>                    | 1.3          |
| <b>Height H (Imperial)</b>                     | 0.67         |
| <b>Panel Thickness Min(Imperial)</b>           | 0.02         |
| <b>Panel Thickness Max(Imperial)</b>           | 0.07         |
| <b>Panel Thickness Min (Metric)</b>            | 0.6          |
| <b>Panel Thickness Max (Metric)</b>            | 1.8          |
| <b>Mounting Hole Diameter D (Imperial)</b>     | 0.25 - 0.26  |
| <b>Mounting Hole Diameter D (Metric)</b>       | 6.3 - 6.7 mm |
| <b>Mounting Hole Diameter D Min (Imperial)</b> | 0.25         |
| <b>Mounting Hole Diameter D Max (Imperial)</b> | 0.26         |
| <b>Mounting Hole Diameter D Max (Metric)</b>   | 6.7          |
| <b>Disc Diameter(Metric)</b>                   | 16.0         |
| <b>Disc Diameter (Imperial)</b>                | 0.63         |

|                                       |  |
|---------------------------------------|--|
| <b>Material</b>                       | Polyamide 6.6 heat stabilized (PA66HS) |
| <b>Material Shortcut</b>              | PA66HS                                 |
| <b>Flammability</b>                   | UL 94 V2                               |
| <b>Operating Temperature (Metric)</b> | -40°F to +221°F (-40°C to +105°C)      |
| <b>Reach Complaint(Article 33)</b>    | Yes                                    |
| <b>ROHS Complaint</b>                 | Yes                                    |
| <b>Package Quantity(Imperial)</b>     | 500                                    |
| <b>Package Quantity (Metric)</b>      | 500                                    |
| <b>Customs Number</b>                 | 3926909988                             |
| <b>Content Unit(BMEcat)</b>           | pcs.                                   |
| <b>Weight (Metric)</b>                | 2                                      |