

## Specification Sheet

Part Number: 148-90049



HelaCon Plus Mini, Push-In Style Wire Connector, Double Spring, 3-Port, (PC), Orange, 400/pkg

**Article Number** 148-90049

**Type** HCPM-3

**Color** Clear (CL) Orange (OG)

**Features & Benefits**

- Spring technology for safe, secure and reliable connections.
- Smaller footprint fits in tight spaces.
- Low insertion force makes installation of solid or stranded copper wire fast and easy.
- Color coded for easy identification of size.
- Each port accepts multiple wire diameters for flexible applications.
- Accepts 12–22 AWG solid wire and 14–22 AWG stranded wire.

**Quantity Per** pack

|                            |   |
|----------------------------|---|
| <b>Product Description</b> | HelaCon Plus Mini Wire Connectors replace traditional twist-on wire connectors. They provide faster, easier and more reliable connection and distribution of cable and conductors in electrical installation applications. Mini connectors have a compact footprint and can be applied tool-free using convenient, push-in simplicity. Internal spring technology is approved for solid and stranded wires. |
| <b>Short Description</b>   | HelaCon Plus Mini, Push-In Style Wire Connector, Double Spring, 3-Port, (PC), Orange, 400/pkg   |
| <b>Global Part Name</b>    | HCPM-3-PC-CL/OG   |
| <b>Length L (Imperial)</b> | 0.65  |
| <b>Length L (Metric)</b>   | 16.5  |
| <b>Width W (Imperial)</b>  | 0.59  |
| <b>Width W (Metric)</b>    | 15.1  |
| <b>Height H (Imperial)</b> | 0.30  |
| <b>Height H (Metric)</b>   | 7.70  |
| <b>Depth D (imperial)</b>  | 0.65  |
| <b>Depth D (metric)</b>    | 16.5  |
| <b>Material</b>            | Polycarbonate (PC)  |

|  |   |
|--|---|
| <b>Material Shortcut</b>               | PC  |
| <b>Flammability</b>                    | UL 94 V0  |
| <b>Halogen free</b>                    | Yes   |
| <b>Operating Temperature (Metric)</b>  | -22°F to +185°F (-30°C to +85°C)  |
| <b>ROHS Complaint</b>                  | Yes   |
| <b>Certification/Specification WEB</b> | UL   ANSI/UL 486-A UL   ANSI/UL 486-C SGS Fimko Ltd   EN 60998-2-2:201 UL   ANSI/UL 486-B VDE   DIN EN 60998-2-2:2005-03 CE   2006/65/EC cULus SGS Fimko Ltd   EN 60998-2-2:2004 Intertek Semko   EN 60998-2-2:2004 ENEC NEMKO AS   EN 60998-2-2:2004 |
| <b>UL Listed (US and Canada)</b>       | Yes   |
| <b>UL Listed (US</b>                   | Yes   |
| <b>Package Quantity(Imperial)</b>      | 400   |
| <b>Package Quantity (Metric)</b>       | 400   |
| <b>Customs Number</b>                  | 8536695050  |