

157-00140



Article Number: 157-00140

Fir Tree Cable Tie, 6.7" Long, 50lbs, 0.24" - 0.26", PA66HIRHS, Black, 500/pkg



Download drawing



Download spec sheet

## Base Data

<b>Local Order Number</b>	157-00140
<b>Type</b>	T50SOSFT6LG-E2
<b>Color</b>	Black (BK)
<b>Features and Benefits</b>	<ul style="list-style-type: none"> <li>• Off-Set design allows bundles to sit off of mounting points to avoid friction against surrounding areas.</li> <li>• Fir tree gives 3 to 1 extraction versus insertion force making them strong and easy to install.</li> <li>• Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation.</li> </ul>
<b>Product Description</b>	<p>HellermannTyton's Off-Set Fir Tree Cable Tie and fixing offers a simple and easy to use method of bundling and fixing cables, the design of the fir tree ensures a positive and secure fixing into panels with thicknesses from .2" - .26" or threaded blind holes.</p> <p>The 'disc' on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.</p>
<b>Short Description</b>	Fir Tree Cable Tie, 6.7" Long, 50lbs, 0.24" - 0.26", PA66HIRHS, Black, 500/pkg

## Product Dimensions

<b>Minimum Tensile Strength (Imperial)</b>	50.0 lbs
<b>Minimum Tensile Strength (Metric)</b>	222.0 N
<b>Length L (Imperial)</b>	6.7 "
<b>Length L (Metric)</b>	167.0 mm
<b>Fixation Method</b>	Fir Tree
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Width W (Metric)</b>	4.6 mm
<b>Height H (Imperial)</b>	0.6 "
<b>Height H (Metric)</b>	16.1 mm
<b>Bundle Diameter Min. (Imperial)</b>	0.04 "
<b>Bundle Diameter Min. (Metric)</b>	1.0 mm
<b>Bundle Diameter Max. (Imperial)</b>	1.4 "
<b>Bundle Diameter Max. (Metric)</b>	35.0 mm
<b>Disc Diameter (Metric)</b>	16.0 mm
<b>Panel Thickness Max. (Imperial)</b>	0.3 "
<b>Panel Thickness Max. (Metric)</b>	8.25 mm
<b>Panel Thickness Min. (Imperial)</b>	0.02 "
<b>Panel Thickness Min. (Metric)</b>	0.6 mm
<b>Mounting Hole Diameter D (Metric)</b>	6.1 - 6.9 mm

Mounting Hole Diameter D Max. 6.9 mm  
(Metric) Mounting Hole Diameter D Min. (Metric) 6.1 mm

## Logistics and Packaging

---

Quantity Per bag  
Package Quantity (Metric) 500 Pieces  
Carton Quantity 2500

## Material and Specifications

---

Material Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)  
Material Shortcut PA66HIRHS  
Flammability UL94 V2  
ROHS Compliant Yes