Specification Sheet

Part Number: 170-03175



Braided Sleeving, Aluminum Laminated Fiberglass, 0.38" Dia, AL/GF, Silver, 100 ft/reel

Article Number	170-03175
Type	BSHTTST38SR
Color	Silver (SR)
Features & Benefits	• A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion. • Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments. • Cuts with ordinary scissors for fast, easy application.
Quantity Per	reel
Product Description	High Temperature Aluminum Laminated Fiberglass Sleeving is a tubular shaped product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to reflect radiant heat away from the sensitive contents inside the tube.

Short Description	Braided Sleeving, Aluminum Laminated Fiberglass, 0.38" Dia, AL/GF, Silver, 100 ft/reel
Global Part Name	BSHTTST38SR-AL/GF-SR
Length L (Imperial)	100.0
Length L (Metric)	30.48
Bundle Diameter Min (Imperial)	0.1
Bundle Diameter Min (Metric)	2.54
Bundle Diameter Max (Imperial)	0.437
Bundle Diameter Max (Metric)	11.1
Diameter D (imperial)	0.38
Diameter D (metric)	9.7
Nominal Diameter (Imperial)	0.38
Nominal Diameter (Metric)	9.7
Wall Thickness WT (Imperial)	0.025
Wall Thickness WT (Metric)	0.64

Material	Aluminum (AL) Glass Fiber (GF)
Material Shortcut	AL GF
Flammability	Non-Flammable
Halogen free	Yes
Operating Temperature (Metric)	-76°F to +491°F (-60°C to +255°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	100
Package Quantity (Metric)	30.48
Customs Number	7019905050
Weight (Metric)	1.1
Weight (Imperial)	2.3
Reel Weight (Imperial)	2.25
Reel Weight (Metric)	1.02

© 2020 HellermannTyton. All Rights Reserved.