

170-03194



Article Number: 170-03194

Aluminum Laminated Fiberglass Wrap, 4-FT Stick, 3/4" Dia., AL; GF, Silver, 15/box



 Download spec sheet

 Download tech sheet

Base Data

|                       |                                                                                                                                                                                                                                                                                                                                            |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Local Order Number    | 170-03194                                                                                                                                                                                                                                                                                                                                  |
| Type                  | BSHTTSW34SB                                                                                                                                                                                                                                                                                                                                |
| Color                 | Silver (SR)                                                                                                                                                                                                                                                                                                                                |
| Features and Benefits | <ul style="list-style-type: none"><li>• A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.</li><li>• Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.</li><li>• Cuts with ordinary scissors for fast, easy application.</li></ul> |
| Product Description   | Aluminum Laminated Fiberglass Wrap sleeving combines the protection of bonded aluminum and fiberglass into a robust solution that deflects radiant heat away from sensitive wires and cables. Wrap-around design allows for fast and easy installation and maintenance.                                                                    |
| Short Description     | Aluminum Laminated Fiberglass Wrap, 4-FT Stick, 3/4" Dia., AL; GF, Silver, 15/box                                                                                                                                                                                                                                                          |

Product Dimensions

|                              |          |
|------------------------------|----------|
| Length L (Imperial)          | 4.0 ft   |
| Length L (Metric)            | 1.22 m   |
| Diameter D (imperial)        | 0.75 "   |
| Diameter D (metric)          | 19.05 mm |
| Nominal Diameter (Imperial)  | 3/4 "    |
| Nominal Diameter (Metric)    | 19.05 mm |
| Wall Thickness WT (Imperial) | 0.042 "  |
| Wall Thickness WT (Metric)   | 1.06 mm  |

Logistics and Packaging

|                           |     |
|---------------------------|-----|
| Quantity Per              | box |
| Package Quantity          | 15  |
| Package Quantity (Metric) | 15  |
| Carton Quantity           | 15  |

Material and Specifications

|                       |                                         |
|-----------------------|-----------------------------------------|
| Material              | Glass fiber with aluminium foil (GF-AL) |
| Material Shortcut     | GF-AL                                   |
| Flammability          | non flammable                           |
| Operating Temperature | -76°F to +491°F (-60°C to +255°C)       |
| ROHS Compliant        | Yes                                     |

