

596-00833

Article Number: 596-00833

Pre-Printed Metal Solar Placard, "DUAL POWER SOURCE", 4.0" X .75", Aluminum, Orange, 5/PK



## Base Data

Local Order Number 596-00833

Type WDPSLBLM5

Color Orange (OG)

**Features and Benefits**

- Made with UV stable inks and materials for durability and weather resistance
- Supplied with aggressive adhesive to ensure long life
- Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections
- Pre-printed labels offer significant time and cost savings over high priced engraved and lead time purchased markers

**Product Description** HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2011) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

**Technical Description** 4.0" X .75" Black text on an Orange background that reads as;" WARNING - DUAL POWER SOURCE SECOND SOURCE IS PV SYSTEM." 5 per pack.

**Short Description** Pre-Printed Metal Solar Placard, "DUAL POWER SOURCE", 4.0" X .75", Aluminum, Orange, 5/PK

## Product Dimensions

Length L (Imperial) 4.0 "

Length L (Metric) 101.6 mm

Width W (Imperial) 4.0 "

Width W (Metric) 101.6 mm

Height H (Imperial) .75 "

Height H (Metric) 19.05 mm

## Logistics and Packaging

Quantity Per pack

Package Quantity 1

Package Quantity (Metric) 5

## Material and Specifications

**Material** Anodized Aluminum (AA)

**Material Shortcut** AA

**Adhesive** 3M 300LSE Ultra High Bond Permanent Acrylic Adhesive

**Adhesive Shortcut** Acrylic

**Adhesive Operating Temperature** from +50°F (from +10°C)

**Halogenfree** Yes

**Operating Temperature** -40°F to +203°F (-40°C to +95°C)

**ROHS Compliant** Yes

**UL Recognized (US)** Yes