

596-00834

Article Number: 596-00834

Pre-Printed Metal Solar Placard, "CAUTION - PV SYSTEM BACKFED", 4.0" X .75", Aluminum, Yellow, 5/PK



Base Data

Local Order Number 596-00834

Type CBACKFEDM5

Color Yellow (YE)

- Features and Benefits**
- Made with UV stable inks and materials for durability and weather resistance
 - Supplied with aggressive adhesive to ensure long life
 - Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections
 - Pre-printed labels offer significant time and cost savings over high priced engraved and lead time purchased markers

Product Description HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2011) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Technical Description 4.0" X .75" Black text on an Yellow background that reads as: "CAUTION - PHOTOVOLTAIC SYSTEM CIRCUIT IS BACKFED." - 5 per pack.

Short Description Pre-Printed Metal Solar Placard, "CAUTION - PV SYSTEM BACKFED", 4.0" X .75", Aluminum, Yellow, 5/PK

Product Dimensions

Length L (Imperial) 4.0 "

Length L (Metric) 101.6 mm

Width W (Imperial) 4.0 "

Width W (Metric) 101.6 mm

Height H (Imperial) .75 "

Height H (Metric) 19.05 mm

Logistics and Packaging

Quantity Per pack

Package Quantity 1

Package Quantity (Metric) 5

Material and Specifications

Material Anodized Aluminum (AA)

Material Shortcut AA

Adhesive 3M 300LSE Ultra High Bond Permanent Acrylic Adhesive

Adhesive Shortcut Acrylic

Adhesive Operating Temperature from +50°F (from +10°C)

Halogenfree Yes

Operating Temperature -40°F to +203°F (-40°C to +95°C)

ROHS Compliant Yes

UL Recognized (US) Yes