Specification Sheet

Part Number: LTM2500C2



Lashing Tie Mount, .73" x 1.5", .25" Screw, PA66HS, Black, 100/pkg

Article Number	151-00358
Type	LTM250
Color	Black (BK)
Features & Benefits	• The strap is parallel to the mount when inserted into the head, providing a fixed insertion point for the cable tie.
Quantity Per	bag
Product Description	The lashing tie mount is designed to snap into the T250 lashing tie. The tie head is assembled perpendicular to the mount. The strap is parallel to the mount when inserted into the head. The lashing tie mount is recommended for indoor or outdoor wall mount cable applications.
Short Description	Lashing Tie Mount, .73" x 1.5", .25" Screw, PA66HS, Black, 100/pkg

Global Part Name	LTM250-PA66HS-BK
Length L (Imperial)	1.5
Length L (Metric)	37.1
Fixation Method	Screw Mounting and Rivet
Width W (Imperial)	0.73
Width W (Metric)	18.5
Cable Ties	T250
Height H (Imperial)	0.38
Height H (Metric)	9.6
Cable Tie Width Max (Imperial)	0.49
Cable Tie Width Max (Metric)	12.5
Mounting Hole Diameter D (Imperial)	0.26
Mounting Hole Diameter D (Metric)	6.6 mm
Mounting Hole Diameter D Max (Metric)	6.6

Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Flammability	UL 94 V2
Operating Temperature (Metric)	-40°F to +257°F (-40°C to +125°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	100
Package Quantity (Metric)	100
Customs Number	3926909988
Content Unit(BMEcat)	pcs.

© 2020 HellermannTyton. All Rights Reserved.