


## Specification Sheet

Part Number: MB4A10C2



Rubber Adhesive Cable Tie Mount, 1.12" x 1.12", Use With T18-T50 Cable Tie, PA66, White, 100/pkg

**Article Number** 151-28421

**Type** MB4A

**Color** White (WH)

**Features & Benefits**

- For use with HellermannTyton T18 - T50 cable ties to provide stability when securing bundles.
- 4-way opening allows cable ties to be installed parallel or perpendicular to bundles.
- The rubber-based adhesive is an economical choice ideal for indoor applications, with a static load weight of 1.1 lb.
- Two predrilled holes extend mounting options and solutions.
- Extended adhesive liner is easy to remove quickly.

**Quantity Per** bag

|  |  |
|--|--|
| <b>Product Description</b>                 | MB4A adhesive mounts are for use with HellermannTyton T18 - T50 Series cable ties to provide stability when securing bundles. The rubber adhesive-backed mounts can be used to secure a bundle and have two predrilled holes to extend mounting options. |
| <b>Short Description</b>                   | Rubber Adhesive Cable Tie Mount, 1.12" x 1.12", Use With T18-T50 Cable Tie, PA66, White, 100/pkg   |
| <b>Global Part Name</b>                    | MB4A-PA66-WH   |
| <b>Length L (Imperial)</b>                 | 1.12   |
| <b>Length L (Metric)</b>                   | 28.5   |
| <b>Fixation Method</b>                     | Screw Mounting and Adhesive  |
| <b>Width W (Imperial)</b>                  | 1.12   |
| <b>Width W (Metric)</b>                    | 28.5   |
| <b>Cable Ties</b>                          | T18 - T50  |
| <b>Height H (Imperial)</b>                 | .22  |
| <b>Height H (Metric)</b>                   | 5.6  |
| <b>Cable Tie Width Max (Imperial)</b>      | 0.18   |
| <b>Cable Tie Width Max (Metric)</b>        | 4.6  |
| <b>Mounting Hole Diameter D (Imperial)</b> | 0.18   |

**Mounting Hole Diameter D (Metric)** 4.6 mm

**Mounting Hole Diameter D Max (Metric)** 4.6

**Mounting Hole Centers (Imperial)** 0.8

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**Adhesive** Synthetic rubber with base of polyethylene foam

**Flammability** UL 94 V2 (excluding adhesive)

**Adhesive Operating Temperature** 0°F to +150°F (-18 °C to +66 °C)

**Operating Temperature (Metric)** -40°F to +185°F (-40°C to +85°C)

**ROHS Complaint** Yes

**Package Quantity(Imperial)** 100

**Package Quantity (Metric)** 100

**Customs Number** 3926909988

