HellermannTyton

Specification Sheet

Part Number: TSR2I-14



Splice Cover, 1-1/4", PVC, 2-Piece, Ivory, 10 Individual/bag

Article Number	250-02141
Type	TSR2-14
Color	Ivory (IV)
Features & Benefits	• Tamper resistant covers with hidden latch provide security while allowing quick entry for cable maintenance. • PVC construction is lightweight, durable and more affordable than metallic raceway systems. • Flexible hinge is designed to reduce stress cracking and discoloration from repeated opening and closing. • Systems and fittings are available in white, office white and ivory to coordinate with a variety of décor. • Fittings incorporate a minimum 1" bend radius to meet TIA/EIA 568-B and 569-A standards.
Quantity Per	bag

Product Description	HellermannTyton surface raceway systems are the ideal solution for routing communication and power cables. No need to break into existing walls - raceway systems are designed to route cable along wall surfaces. Made of a PVC material, components are durable and affordable; and the one-piece construction and adhesive tape backing make positioning and mounting easy. HellermannTyton offers a low voltage TSR system and a power rated TSRP system that are available in three different diameters to accommodate different cable and wire bundle and conduit sizes. Both systems include a complete line of fittings and junction boxes that allow for clean and professional installations. TSR surface raceway systems can be used to route a variety of communication cable, including high speed UTP and fiber optic cable.
Short Description	Splice Cover, 1-1/4", PVC, 2-Piece, Ivory, 10 Individual/bag
Global Part Name	TSR2-14-PVC-BGE
Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
Flammability	UL 94 V0
Halogen free	No
Operating Temperature (Metric)	+122°F (+50°C)
Reach Complaint(Article 33)	No
ROHS Complaint	Yes
Package Quantity(Imperial)	10

Package Quantity (Metric)	10
Customs Number	3925900000

© 2020 HellermannTyton. All Rights Reserved.