

**PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION**

**Part Number:** [0192030379](#)  
**Status:** **Active**  
**Overview:** Standard Quick-Disconnect Terminals  
**Description:** Krimptite Quick Disconnect, Female, Steel, 483°C (900° F), 10-12 AWG, Tab 6.35mm

**Documents:**

[Drawing \(PDF\)](#) [Product Specification PS-19902-013-001 \(PDF\)](#)  
[Product Specification PS-19902-011-001 \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

**General**

Product Family Quick Disconnects  
 Series [19203](#)  
 Crimp Quality Equipment Yes  
 Insulated No  
 Overview [Standard Quick-Disconnect Terminals](#)  
 Product Name Krimptite  
 Type Quick Disconnect  
 UPC 822348424689

**Physical**

Barrel Type Closed  
 Gender Female  
 Glow-Wire Capable No  
 Insulation None  
 Lock to Mating Part None  
 Material - Metal Steel  
 Material - Plating Mating Nickel  
 Material - Plating Termination Nickel  
 Net Weight 0.670/g  
 Orientation Straight  
 Packaging Type Bag  
 Tab Thickness 0.80mm  
 Tab Width 7.70mm  
 Temperature Range - Operating 483°C  
 Wire Size AWG 10, 12

**Electrical**

Voltage - Maximum N/A

**Material Info**

**Reference - Drawing Numbers**

Product Specification PS-19902-011-001, PS-19902-013-001  
 Sales Drawing SD-19203-025



Series image - Reference only

**EU ELV**

**Not Relevant**

**EU RoHS**

**Not Reviewed**

**REACH SVHC**

Not Reviewed

**Halogen-Free**

**Status**

**Not Reviewed**

For more information, please visit [Contact US](#)

China ROHS

Not Reviewed

ELV

Not Relevant

RoHS Phthalates

Not Reviewed

**Search Parts in this Series**

[19203 Series](#)

**Application Tooling | [FAQ](#)**

*Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.*

**Global**

Description	Product #
Hand Tool for High Temperature Female Quick Disconnects	<a href="#">640031500</a>