

DE2E3KH102MN3A

" # " indicates a package specification code.

Available  

< List of part numbers with package codes >
DE2E3KH102MN3A

Shape



| | |
|---------------------------------|------------------------|
| L size or outer diameter D (mm) | 8.0 mm max. |
| Lead spacing F | 7.5 ± 1.0mm |
| Product thickness T | 7.0mm max. |
| Lead diameter d | 0.6 ± 0.05mm |
| Paint dripping e | Up to the end of crimp |

Specifications

| | |
|--|--------------|
| Capacitance | 1000pF ± 20% |
| Rated voltage | 250Vac |
| Temperature characteristics (complied standard) | E(JIS) |
| Capacitance change rate | +20/-55% |
| Temperature range of temperature characteristics | -25 to 85 |
| Operating temperature range | -25 to 125 |

Notes

X1/Y2 Class Certified Products

References

| Packaging | Specifications | Minimum quantity |
|-----------|-----------------------|------------------|
| | Ammo pack taping type | 900 |

Attention

- 1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it ' s specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2.This datasheet has only typical specifications because there is no space for detailed specifications. Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.