

Shock protection - EMLPR (80X42) - 0800357

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Shock protection, Sheet, transparent, unlabeled, mounting type: adhesive, lettering field size: 80 x 42 mm

Your advantages

- High level of mechanical and chemical stability
- Suitable for permanent outdoor use
- Extremely thick, yet flexible and transparent label made from halogen-free PU
- Stuck over labels or markers that have been labeled to protect them

Key Commercial Data

Packing unit	10 pc
GTIN	 4 046356 612470
GTIN	4046356612470

Technical data

Dimensions

Length (b)	42 mm
Width (a)	80 mm

Ambient conditions

Ambient temperature (operation)	-40 °C ... 90 °C
Recommended storage conditions	18-26 °C / 60 % relative humidity.

General

Color	transparent
Components	halogen-free
Material	PUR
Number of individual labels	6
Number of individual labels per row	1

Shock protection - EMLPR (80X42) - 0800357

Technical data

General

Adhesive	Acrylic
Test for substances that would hinder coating with paint or varnish	VW PV 3.10.7:2005-02
Result	Test passed
Test specification weathering-resistance	Following ISO 4892-2:2013-03
Test duration	4000 h
Alternating condensation climate with SO2 test specification	following DIN 50018:2013-05
Climate level	AHT 1.0 S
Cycles	2
Condensation test result	Test passed
Foil strength	210 µm
Marking mounting type	adhesive

Environmental Product Compliance

	1-Methyl-2-pyrrolidone (NMP) 872-50-4
	2-(2H-benzotriazol-2-yl)-4,6-ditertpentylphenol (UV-328) 25973-55-1

Phoenix Contact 2019 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>