

## Marker for terminal blocks - UC2-TM 4 - 0821713

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID, BLUEMARK ID COLOR, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snap into tall marker groove, for terminal block width: 4 mm, lettering field size: 3.45 x 8.75 mm

### Why buy this product

- The UC2-TM ... UniCard labeling range includes markers for Wago terminal blocks
- The markers, which are supplied in uniform sheets, can be labeled quickly and easily using the BLUEMARK LED
- Labeling service: Phoenix Contact can custom-label all UniCard markers according to your requirements
- The multi-section marking strips are easy to fit and can be easily separated if required
- The sheets provide space for including function texts
- The markers support multi-line labeling



### Key Commercial Data

|                        |   |
|------------------------|---|
| Packing unit           | 10 STK  |
| Minimum order quantity | 10 STK  |
| GTIN                   | <br>4 046356 300667 |
| GTIN                   | 4046356300667   |

### Technical data

#### Dimensions

|           |      |
|-----------|------|
| Width (a) | 4 mm |
|-----------|------|

#### Ambient conditions

|                                 |   |
|---------------------------------|---|
| Ambient temperature (operation) | -40 °C ... 120 °C   |
| Recommended storage conditions  | 23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended. |

#### General

|            |                                |
|------------|--------------------------------|
| Color      | white                          |
| Type       | high                           |
| Components | free from silicone and halogen |

## Marker for terminal blocks - UC2-TM 4 - 0821713

### Technical data

#### General

|   |                                     |
|---|-------------------------------------|
| Flammability rating according to UL 94                              | V2                                  |
| Material  | PA                                  |
| RoHS compliant  | Yes                                 |
| Wipe resistance   | DIN EN 61010-1 (VDE 0411-1)         |
| Number of individual labels   | 120                                 |
| Number of individual labels per row                                 | 15                                  |
| Test for substances that would hinder coating with paint or varnish | VW PV 3.10.7:2005-02                |
| Result  | Test passed                         |
| Test specification weathering-resistance                            | Following ISO 4892-2:2013-03        |
| Test duration   | 96 h                                |
| Wipe resistance test result   | Test passed                         |
| Salt spray test specification                                       | DIN EN 60068-2-11:2000-02           |
| Test duration   | 96 h                                |
| Salt spray testing result   | Test passed                         |
| Wipe resistance of test specification inscriptions                  | DIN EN 61010-1 (VDE 0411-1):2011-07 |
| Result  | Test passed                         |
| Marking mounting type   | snap into tall marker groove        |
| Result  | Test passed                         |
| Oxygen index (DIN EN ISO 4589-2)                                    | 28,2%                               |
| Class I   | 3                                   |
| Class F   | 2                                   |
| R22   | HL 1 - HL 2                         |
| R23   | HL 1 - HL 2                         |
| R24   | HL 1 - HL 2                         |

#### Standards and Regulations

|  |                                     |
|--|-------------------------------------|
| Wipe resistance  | DIN EN 61010-1 (VDE 0411-1)         |
| Flammability rating according to UL 94                 | V2                                  |
| Fire protection for rail vehicles (DIN EN 45545-2) R22 | HL 1 - HL 2 HL 1 - HL 2 HL 1 - HL 2 |
| Fire protection for rail vehicles (DIN EN 45545-2) R23 | HL 1 - HL 2 HL 1 - HL 2 HL 1 - HL 2 |
| Fire protection for rail vehicles (DIN EN 45545-2) R24 | HL 1 - HL 2 HL 1 - HL 2 HL 1 - HL 2 |
| Fire protection for rail vehicles (DIN EN 45545-2) R26 | HL 1 - HL 2 HL 1 - HL 2 HL 1 - HL 2 |

Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>