

# Cable gland - G-INESR-M40-M68N-NEPDS-S - 1415195

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable gland, cable gland material: Nickel-plated brass, application: Standard, external cable diameter 16 mm ... 28 mm, shielding: no, connecting thread: M40 x 1.5, color: silver, with external strain relief, with O-ring


The figure shows version G-INESR-M25-M68N-NEPDS-S

## Your advantages

- Weatherproof sealing material
- Halogen-free



## Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 038681
GTIN	4055626038681

## Technical data

### Dimensions

Length	54 mm
Length without connecting thread	46 mm
Wrench size, union nut	46 mm
Wrench size, support	46 mm
Hexagon angular dimension	51 mm
Length of the connecting thread	8 mm
Feed-through hole diameter	40.1 mm ... 40.3 mm
External cable diameter	16 mm ... 28 mm
	17.4 mm ... 26.4 mm (for UL 514 B)
Clamping range of the strain relief clip	16.00 mm ... 28.00 mm

### Ambient conditions

Degree of protection (IP)	IP68 (5 bar / 0.5 h)
---------------------------	----------------------

# Cable gland - G-INESR-M40-M68N-NEPDS-S - 1415195

## Technical data

### Ambient conditions

	IP69 (DIN EN 60529 / IEC 60529)
Ambient temperature (operation)	-40 °C ... 100 °C (static)

### General

Type	with external strain relief
No. of conductors	1
Cable gland material	Nickel-plated brass
Material, insert	PA
Cable seal material	EPDM
O-ring material	EPDM
Shielded	no
Thread type connection side	M40 x 1.5
Thread type on connection side	M40
Torque	20 Nm (Union nut: EN 62444)
	20 Nm (Support: EN 62444)
	0.5 Nm (Screw for clip)
Color	silver
Impact category	6
Execution of the strain relief	B
Manufacturer	WISKA
Manufacturer Designation	EMSKVZ 40

### Standards and Regulations


Halogen-free	yes
--------------	-----

### Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

## Drawings

Dimensional drawing



# Cable gland - G-INESR-M40-M68N-NEPDS-S - 1415195

## Approvals

### Approvals

---

#### Approvals





UL Recognized / cUL Recognized / GOST-R / cULus Recognized

---

#### Ex Approvals

---

### Approval details

UL Recognized		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a>	E179850
cUL Recognized		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a>	E179850
GOST-R			POCC DE.A*98.H12052
cULus Recognized			

---

Phoenix Contact 2019 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>