

Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation at <http://www.download.phoenixcontact.com>. The General Terms and Conditions of Use apply to Internet downloads.

## ► Extract from the online catalog



Sensor/actuator box, with LED, with master cable, markers and single-occupied slots

Order No.	1695168
Ord designation	SACB-8/ 8-L- 5,0PUR
EAN	4017918177645
Pack	1 Pcs.
Customs tariff	85444190
Catalog page information	Page 129 (PC-2005)

## ► Technical data

### General data

Nominal voltage $U_N$	24 V DC
Max. operating voltage $U_{max}$	30 V DC
Ambient temperature (operation)	-25 ° C ... 75 ° C
Degree of protection	IP65/IP67
Number of positions	4
Max. current carrying capacity per path	2 A
SACB total current	12 A
Operating current of the indicator elements	$\leq 5$ mA
Number of slots	8
Sensor/actuator connection system	M 12 female connector

### Local diagnostics function

Local diagnostics	Supply voltage per module LED green
Local diagnostics	Status display I/O Yellow LED

**Master cable data**

Type of connection	Fixed connection
Fixed cable length	5 m
Cable type	Master cable suitable for flexible cable conduit
Ambient temperature (operation)	-30 ° C ... 90 ° C (for fixed installation)
Ambient temperature (operation)	-5 ° C ... 70 ° C (for flexible installation)
Signal line cross section, flexible	0.34 mm <sup>2</sup>
Power supply cross section, flexible	0.75 mm <sup>2</sup> (3x)
External diameter	9.2 mm
AWG power supply	18
AWG signal line	22

**Insulation material**

Insulating material	PA 6.6
Inflammability class acc. to UL 94	V0

---

## ► Certificates

---

### Certificate logos



---

#### **CUL**

Nominal voltage $U_N$	120 V
AWG/kcmil	22-16

---

#### **UL**

Nominal voltage $U_N$	120 V
AWG/kcmil	22-16

---



---

▶ **Accessories**

---

Item	Designation	Description
<b>Assembly</b>		
1680539	PROT-M12	Sealing cap for closing unoccupied connections M12

---

## ► Address

---

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Phone +49 5235 3 00  
Fax +49 5235 3 1200  
<http://www.phoenixcontact.com>  
Phoenix Contact  
Technical modifications reserved;