

Relay base - SIM-AMSC1 - 2271390


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Plug-in base for standard I/O modules, Generation 4 from Opto 22, can be labeled with marker pins BN or BNB



RoHS

Key Commercial Data

Packing unit	50 STK
GTIN	 4 017918 054274
GTIN	4017918054274

Technical data

Dimensions

Pin dimensions	1,1 x 0,5 mm
Hole diameter	1.4 mm

General

Nominal voltage U_N	250 V AC
	380 V AC
Nominal current I_N	5 A
Color	green
Insulating material	PA
Standards/regulations	DIN VDE 0110b, Gr. C for 250 V DC

Standards and Regulations

Connection in acc. with standard	UL
Standards/regulations	DIN VDE 0110b, Gr. C for 250 V DC

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50

Relay base - SIM-AMSC1 - 2271390


Technical data

Environmental Product Compliance


	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"
--	---

Drawings

Dimensional drawing



Schematic diagram



Contacts in the plug-in socket:
 A = with metal
 B = without metal

Approvals

Approvals

Approvals

UL Recognized / EAC

Ex Approvals

Approval details

UL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 113228
Nominal voltage UN	300 V		
Nominal current IN	5 A		

EAC		RU C- DE.A*30.B.01082
-----	--	--------------------------

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>