


Potential distributors - UM 25-PVB 2/12ICV/SO19 - 2298331

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

VARIOFACE module, with COMBICON connectors and two potentials (+ -) for potential distribution, for mounting on NS 35/7.5 or NS 32



Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 587789
GTIN	4017918587789

Technical data

Dimensions

Width	25 mm
Height	97 mm
Depth	42 mm

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
---------------------------------	------------------

General

Nominal voltage U_N	230 V AC/DC
Total current	12 A
Mounting position	any
Designation	Air clearances and creepage distances
Standards/regulations	DIN EN 50178: 1998-04
Rated surge voltage	2.1 kV (1.2/50 μ s)
Rated insulation voltage	230 V
Degree of pollution	2
Overvoltage category	II
Degree of protection	IP00

Potential distributors - UM 25-PVB 2/12ICV/SO19 - 2298331

Technical data

Connection data, supply

Number of connections	2
-----------------------	---

Connection data, distribution

Number of connections	12
-----------------------	----

Standards and Regulations

Designation	Air clearances and creepage distances
Standards/regulations	DIN EN 50178: 1998-04
Rated insulation voltage	230 V
Rated surge voltage	2.1 kV (1.2/50 µs)
Insulation	Functional insulation
Degree of pollution	2
Overvoltage category	II

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		RU C- DE.A*30.B.01742
-----	---	--------------------------

Phoenix Contact 2019 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>