


**CABLE-FCN40/4X14/ 2,0M/S7-IN**

Order No.: 2321279

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2321279>

Assembled round cable for coupling 4x8 inputs of S7-300 card 6ES7 321-1BP00-0AA0. The system cable has one 40-pos. Fujitsu strip and four 14-pos. FLK strips, length 2 m

**Commercial data**

GTIN (EAN)	 4 046356 332071
sales group	I680
Pack	1 pcs.
Customs tariff	85444290
Catalog page information	Page 233 (IF-2011)

**Product notes**

WEEE/RoHS-compliant since:  
11/30/2007



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

**Technical data****General**

Nominal voltage $U_N$	< 50 V AC
	60 V DC
Max. current carrying capacity per path	1 A

Max. conductor resistance	0.16 $\Omega$ /m
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Plug connector, control side	Fujitsu plug connector
Plug connector, module side	IDC/FLK socket strip (2.54 mm)
Fixed cable length	2 m
Single wire, cross section	0.14 mm <sup>2</sup>
AWG	26
Conductor construction: Number of litz wires:	7
Single wire, material	Cu tin-plated
External diameter	6.3 mm
Shielding	no

**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2012 Phoenix Contact  
Technical modifications reserved;