

► General data



SUB-D connector with one cable entry, 15-pos., male version

Order number	2761606
Type	SUBCON 15/M-SH

Barcode number	4017918101671
Unit pack	1 Piece
Customs tariff	85369010000

► Technical data

General data

Nominal voltage U_N	60 V AC/DC
Nominal current I_N	1 A
Insertion/withdrawal cycles	> 200
Max. cable diameter	10 mm
Min. cable diameter	4 mm
SUBCON fixing screws	4-40 UNC
Tightening torque	0.4 Nm
Ambient temperature (operation)	-20 °C ... 75 °C
Housing material	ABS, metal-plated
Pin assignment	all 1:1

Connection data

Connection	D-SUB connection
Number of positions	15
Type of connection	D-SUB male connector
Connection	PCB connection
Type of connection	Screw connection
Min. conductor cross section, rigid	0.14 mm ²
Conductor cross section, rigid max.	1.5 mm ²
Conductor cross section flexible min.	0.14 mm ²
Max. conductor cross section, flexible	1 mm ²
Min. conductor cross section AWG/kcmil	26
Conductor cross section AWG/kcmil max	16
Stripping length	5 mm
Tightening torque	0.4 Nm

► Certificates

UL


Nominal voltage U_N	125 V
Nominal current I_N	1 A
AWG/kcmil	30-16

CUL

Nominal voltage U_N	125 V
Nominal current I_N	1 A
AWG/kcmil	30-16

▸ Drawings

Dimensioned drawing



Approval logo



▶ Accessories

Item	Designation	Description
Assembly		
2799694	SUBCON-SHORT-SCREW	Optional fixing screw, short (w/o knurl)

► Address

Phoenix Contact GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel + 49 - (0) 52 35 - 3-00
Fax + 49 - (0) 52 35 - 3-4 12 00
www.phoenixcontact.com

© Phoenix Contact
Technical modifications reserved