

Lightning arrester type 1 - FLT 35 CTRL-1.5 - 2816894

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Type 1 / Class I / B arrester (lightning current arrester) with encapsulated arc chopping spark gap and ignition electronics, 1-channel. Protection level: 1.5 kV. Housing width: 17.5 mm (1 Div.)

The illustration shows version FLT 35 CTRL-0,9/I



Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 606220
Weight per Piece (excluding packing)	188.6 g
Custom tariff number	85363030
Country of origin	Germany
Note	Made to Order (non-returnable)

Technical data

Dimensions

Height	88.6 mm
Width	17.6 mm
Depth	66.2 mm
Horizontal pitch	1 Div.

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 85 °C
Permissible humidity (operation)	≤ 95 %

General

Housing material	PA
Inflammability class according to UL 94	V0
Color	black
Standards for clearances and creepage distances	IEC 60664-1

Lightning arrester type 1 - FLT 35 CTRL-1.5 - 2816894

Technical data

General

	VDE 0110-1
Mounting type	DIN rail: 35 mm
Type	Rail-mountable module, one-piece
Surge protection fault message	None
Direction of action	1L-N/PE

Protective circuit

IEC test classification	I
	T1
EN type	T1
Maximum continuous operating voltage U_C	440 V AC
Maximum continuous operating voltage U_C (L-N)	440 V AC
Maximum continuous operating voltage U_C (L-PEN)	440 V AC
Nominal frequency f_N	50 Hz
	60 Hz
Residual current I_{PE}	≤ 0.5 mA
Operating effective current I_C at U_N	≤ 0.5 mA
Nominal discharge current I_n (8/20) μ s	35 kA
Nominal discharge current I_n (8/20) μ s (L-N)	35 kA
Nominal discharge current I_n (8/20) μ s (L-PEN)	35 kA
100% lightning impulse sparkover voltage (1.2/50) μ s	≤ 1.5 kV
100% lightning impulse sparkover voltage (1.2/50) μ s (L-N)	≤ 1.5 kV
100% lightning impulse sparkover voltage (1.2/50) μ s (L-PEN)	≤ 1.5 kV
Voltage protection level U_p	≤ 1.5 kV
Voltage protection level U_p (L-N)	≤ 1.5 kV
Voltage protection level U_p (L-PEN)	≤ 1.5 kV
Response time t_A	≤ 100 ns
Response time t_A (L-N)	≤ 100 ns
Response time t_A (L-PE)	≤ 100 ns
Max. backup fuse with branch wiring	125 A (gL)
Short-circuit resistance I_p with max. backup fuse (effective)	25 kA
Follow current interrupt rating I_{fi} (L-N)	3 kA (260 V)
Follow current quenching capacity I_{fi} (L-PEN)	3 kA (260 V)

Connection, protective circuit

Connection method	Screw connection
Connection type IN	Biconnect screw terminal block
Connection type OUT	Biconnect screw terminal block
Connection method	Biconnect terminal block
Screw thread	M5
Tightening torque	4.5 Nm

Lightning arrester type 1 - FLT 35 CTRL-1.5 - 2816894

Technical data

Connection, protective circuit

Stripping length	14.5 mm
Conductor cross section flexible min.	0.5 mm ²
Conductor cross section flexible max.	25 mm ²
Conductor cross section solid min.	0.5 mm ²
Conductor cross section solid max.	35 mm ²
Conductor cross section AWG min.	20
Conductor cross section AWG max.	2

Standards and Regulations

Standards/regulations	IEC 61643-1 1998-02
	E DIN VDE 0675-6 1989-11
	E DIN VDE 0675-6/A1 1996-03
	E DIN VDE 0675-6/A2 1996-10
	IEC 61312-1 1995-02

Classifications

eCl@ss

eCl@ss 4.0	27140201
eCl@ss 4.1	27140201
eCl@ss 5.0	27140201
eCl@ss 5.1	27140201
eCl@ss 6.0	27140201
eCl@ss 7.0	27140201
eCl@ss 8.0	27130802

ETIM

ETIM 2.0	EC000381
ETIM 3.0	EC000381
ETIM 4.0	EC000381
ETIM 5.0	EC000381

UNSPSC

UNSPSC 6.01	30212010
UNSPSC 7.0901	39121610
UNSPSC 11	39121610
UNSPSC 12.01	39121610
UNSPSC 13.2	39121620

Approvals

Approvals

Lightning arrester type 1 - FLT 35 CTRL-1.5 - 2816894

Approvals

Approvals

EAC

Ex Approvals

Approvals submitted

Approval details

EAC

Accessories

Accessories

Device marking

Zack marker strip - ZBN 18:UNBEDRUCKT - 2809128



Zack marker strip, Strip, white, unlabeled, can be labeled with: Plotter, Mounting type: Snap into tall marker groove, for terminal block width: 18 mm, Lettering field: 18 x 5 mm

End block

End clamp - CLIPFIX 35 - 3022218



Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, width: 9.5 mm, color: gray

Labeled device marker

Marker for terminal blocks - ZBN 18,LGS:ERDE - 2749589




Marker for terminal blocks, Strip, white, labeled, Horizontal: Grounding symbol, Mounting type: Snap into tall marker groove, for terminal block width: 18 mm, Lettering field: 18 x 5 mm

Lightning arrester type 1 - FLT 35 CTRL-1.5 - 2816894

Drawings

Dimensional drawing



Circuit diagram

