

► General data



Basic termination blocks with screw connection for NS 32 and NS 35/7.5 mounting rail, with end cover, for ST-REL..., ST-OV... and ST-OE... plugs, 7-pos.

Order number	2820178
Type	URELG 7

Barcode number	4017918076801
Unit pack	10 Pcs.
Customs tariff	85369010000

► Technical data

General data

Number of positions	7
Nominal voltage U_N	400 V (Voltage is determined by the coupling connector.)
Nominal current I_N	16 A (Current is determined by the coupling connector.)
Color	gray
Insulating material	PA

Connection data


Min. conductor cross section, rigid	0.2 mm ²
Conductor cross section, rigid max.	4 mm ²
Conductor cross section flexible min.	0.2 mm ²
Max. conductor cross section, flexible	4 mm ²
Min. conductor cross section AWG/kcmil	24
Conductor cross section AWG/kcmil max	12
Type of connection	Screw connection
Stripping length	9 mm
Screw thread	M 3

Dimensions


Width with lid	45.6 mm
----------------	---------

▸ Drawings

Dimensioned drawing



Schematic diagram



► Accessories

Item	Designation	Description
Assembly		
1201442	E/UK	End clamp, for supporting the electronic base, if mounted vertically, 2 end clamps are required in each case
Bridges		
2820916	DB 50- 90 BK	Wire bridge, 50-position, divisible, for bridging identical inputs and outputs, 0.5 mm ² , insulation: blue
2821180	DB 50- 90 BU	Wire bridge, 50-position, divisible, for bridging identical inputs and outputs, 0.5 mm ² , insulation: black
2820929	DB 50- 90 GY	Wire bridge, 50-position, divisible, for bridging identical inputs and outputs, 0.5 mm ² , insulation: gray

► Address

Phoenix Contact GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel + 49 - (0) 52 35 - 3-00
Fax + 49 - (0) 52 35 - 3-4 12 00
www.phoenixcontact.com

© Phoenix Contact
Technical modifications reserved