

► General data



Relay connector, equipped with miniature switching relay, contacts (AgCdO): medium to large loads, 1 N/O contacts, input voltage 24 V AC/DC, with light indicator, can be plugged on basic termination blocks

Order number	2823625
Type	ST-REL2-KG 24/1
Barcode number	4017918077464
Unit pack	10 Pcs.
Customs tariff	85364190990

► Technical data

Coil side

Nominal input voltage U_N	24 V AC/DC
Input voltage range in reference to U_N	0.8 ... 1.1
Nominal input current at U_N	21 mA
Typical response time	7 ms (With DC)
Typical release time	11 ms (With DC)
Operating voltage display	Yes
Protective circuit/component	Bridge rectifier, varistor

Contact side


Contact type	Single contact, 1 N/O contact
Contact material	Silver cadmium oxide (AgCdO)
Maximum switching voltage	250 V AC/DC
Maximum inrush current	8 A
Limiting continuous current	6 A
Power rating (ohmic load) max.	95 W (For 24 V DC)
Power rating (ohmic load) max.	50 W (For 48 V DC)
Power rating (ohmic load) max.	45 W (For 60 V DC)
Power rating (ohmic load) max.	35 W (For 110 V DC)
Power rating (ohmic load) max.	55 W (For 220 V DC)
Power rating (ohmic load) max.	1500 VA (for 250 V AC)

General data

Width	14.6 mm
Test voltage relay winding/relay contact	2.5 kV AC
Ambient temperature (operation)	-20 °C ... 50 °C
Operating mode	100% operating factor
Service life mechanical	approx. 2×10^7 cycles
Standards/regulations	DIN VDE 0110b: 1979-02, Gr. C for 250 V DC
Standards/regulations	DIN VDE 0160 and IEC 60 255/DIN VDE 0435 (in relevant parts)

▶ Drawings

Circuit diagram



► Additional products

General

2833107
2777030
2820262
2820835
2829904

QT 1,5RELG2
UDK-RELG 2
URELG 2
URELG 2-PMTK
ZFK-RELG 2

► Address

Phoenix Contact GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel + 49 - (0) 52 35 - 3-00
Fax + 49 - (0) 52 35 - 3-4 12 00
www.phoenixcontact.com

© Phoenix Contact
Technical modifications reserved