

Relay Module - PR2-RSC3-LDP-24DC/2X21 - 2834643

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Preassembled relay modules with screw connection, consisting of: relay base, industrial relay with integrated LED, free-wheeling diode and engage/disengage manual actuate lever, and retaining bracket. Input voltage: 24 V DC, two PDTs, 10 A

Your advantages

- ✓ With DC types, freewheeling diode is integrated in relay
- ✓ Relay with detectable manual operation and status LED
- ✓ Logical contact arrangement thanks to 1/3-level relay base
- ✓ Mechanical switch position indicator
- ✓ 4 PDT types with multi-layer gold contacts



Key Commercial Data

| | |
|--------------|---|
| Packing unit | 5 pc |
| GTIN |  4 046356 044530 |
| GTIN | 4046356044530 |

Technical data

Note

| | |
|-------------------------|---|
| Utilization restriction | EMC: class A product, see manufacturer's declaration in the download area |
|-------------------------|---|

Dimensions

| | |
|--------|---------|
| Width | 27 mm |
| Height | 78.5 mm |
| Depth | 86 mm |

Ambient conditions

| | |
|---|------------------|
| Ambient temperature (operation) | -25 °C ... 60 °C |
| Ambient temperature (storage/transport) | -25 °C ... 70 °C |

Coil side

Relay Module - PR2-RSC3-LDP-24DC/2X21 - 2834643

Technical data

Coil side

| | |
|---|---------------|
| Nominal input voltage U_N | 24 V DC |
| Input voltage range in reference to U_N | see diagram |
| Typical input current at U_N | 38 mA |
| Typical response time | 13 ms |
| Typical release time | 14 ms |
| Protective circuit | Damping diode |
| Operating voltage display | Green LED |
| Power dissipation for nominal condition | 0.91 W |

Contact side

| | |
|---------------------------------------|------------------------|
| Contact type | 2 PDT |
| Type of switch contact | Single contact |
| Contact material | Ag |
| Maximum switching voltage | 250 V AC/DC |
| Minimum switching voltage | 5 V |
| Min. switching current | 1 mA |
| Maximum inrush current | 20 A (15 ms) |
| Limiting continuous current | 10 A |
| Interrupting rating (ohmic load) max. | 2500 VA (for 250 V AC) |
| | 240 W (at 24 V DC) |
| | 144 W (at 48 V DC) |
| | 108 W (at 60 V DC) |
| | 72 W (at 110 V DC) |
| | 110 W (at 220 V DC) |

General

| | |
|--|---------------------------|
| Test voltage relay winding/relay contact | 2 kV (50 Hz, 1 min.) |
| Test voltage relay contact/relay contact | 2 kV (50 Hz, 1 min.) |
| Operating mode | 100% operating factor |
| Mechanical service life | 5×10^7 cycles |
| Service life, electrical | see diagram |
| Mounting position | any |
| Assembly instructions | In rows with zero spacing |

Connection data input side

| | |
|----------------------------------|--|
| Connection name | Coil side |
| Connection method | Screw connection |
| Stripping length | 7 mm |
| Screw thread | M3 |
| Conductor cross section solid | 0.14 mm ² ... 2.5 mm ² |
| Conductor cross section flexible | 0.14 mm ² ... 2.5 mm ² |
| Conductor cross section AWG | 26 ... 14 |

Relay Module - PR2-RSC3-LDP-24DC/2X21 - 2834643

Technical data

Connection data output side

| | |
|----------------------------------|--|
| Connection name | Contact side |
| Connection method | Screw connection |
| Stripping length | 7 mm |
| Screw thread | M3 |
| Conductor cross section solid | 0.14 mm ² ... 2.5 mm ² |
| Conductor cross section flexible | 0.14 mm ² ... 2.5 mm ² |
| Conductor cross section AWG | 26 ... 14 |

Standards and Regulations

| | |
|-----------------------|-----------|
| Standards/regulations | IEC 60664 |
| | EN 50178 |
| Pollution degree | 3 |
| Overvoltage category | II |


Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally Friendly Use Period = 50 years |
| | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

Drawings

Relay Module - PR2-RSC3-LDP-24DC/2X21 - 2834643


Circuit diagram



DC coils

Relay Module - PR2-RSC3-LDP-24DC/2X21 - 2834643


Diagram



Operating voltage range of relay $T_u=T_{coil}$

Relay Module - PR2-RSC3-LDP-24DC/2X21 - 2834643


Diagram



AC interrupting rating

Relay Module - PR2-RSC3-LDP-24DC/2X21 - 2834643


Diagram



DC interrupting rating

Relay Module - PR2-RSC3-LDP-24DC/2X21 - 2834643

Diagram



- ① 250 V AC, ohmic load
- ② 30 V DC, ohmic load

Electrical service life

Articles in set

Relay base - PR2-BSC3/4X21 - 2833576



Relay base PR2-B, for industrial relay REL-IR with 2 or 4 PDT, 1/3-level version, screw connections, connection facility for input/interference suppression modules, for mounting on NS 35/7.5

Single relay - REL-IR/LDP- 24DC/2X21 - 2834025



Pluggable industrial relays with power contacts, 2 PDT, test button, status LED, free-wheeling diode, mechanical switch position indicator, polarity A1+, A2-, input voltage 24 V DC

Relay Module - PR2-RSC3-LDP-24DC/2X21 - 2834643

Articles in set

Retaining bracket - EL2-P35 - 2833592



Relay retaining bracket, with eject function and integrated equipment marking area (8 x 25 mm), to suit relay base PR2, for 35 mm high industrial relay

Marker labels - MP 2 - 2833644



Equipment marker, labeling surface 9 x 25 mm

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27371100 |
| eCl@ss 4.1 | 27371100 |
| eCl@ss 5.0 | 27371600 |
| eCl@ss 5.1 | 27371600 |
| eCl@ss 6.0 | 27371600 |
| eCl@ss 7.0 | 27371601 |
| eCl@ss 8.0 | 27371601 |
| eCl@ss 9.0 | 27371601 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC001437 |
| ETIM 3.0 | EC001437 |
| ETIM 4.0 | EC001437 |
| ETIM 5.0 | EC001437 |
| ETIM 6.0 | EC001437 |
| ETIM 7.0 | EC001437 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211916 |
| UNSPSC 7.0901 | 39121515 |
| UNSPSC 11 | 39121515 |
| UNSPSC 12.01 | 39121515 |
| UNSPSC 13.2 | 39122334 |
| UNSPSC 18.0 | 39122334 |

Relay Module - PR2-RSC3-LDP-24DC/2X21 - 2834643

Classifications

UNSPSC

| | |
|-------------|----------|
| UNSPSC 19.0 | 39122334 |
| UNSPSC 20.0 | 39122334 |
| UNSPSC 21.0 | 39122334 |

Approvals

Approvals


Approvals

EAC / EAC

Ex Approvals

Approval details

| | | |
|-----|---|-----------------|
| EAC |  | TR_TS_D_00573_c |
|-----|---|-----------------|

| | | |
|-----|---|-------------------------|
| EAC |  | RU*C- DE.*08.B.00010 |
|-----|---|-------------------------|

Phoenix Contact 2020 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>