

## Fuse set - FUSE/TE5/2A/F-5PCS - 2906444

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Plug-in fuse (TE5<sup>®</sup>); nominal current: 2 A; tripping behavior: fast-blow (F)

500 mA version shown



### Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 337449
GTIN	4055626337449

### Technical data

#### General

Number of fuses in the set	5
Nominal voltage $U_N$	$\leq 250$ V AC/DC
Nominal current $I_N$	2 A
Tripping characteristic	fast-blow (F)

### Classifications

#### eCl@ss

eCl@ss 10.0.1	27142008
eCl@ss 5.0	27142007
eCl@ss 5.1	27142007
eCl@ss 6.0	27142000
eCl@ss 7.0	27142008
eCl@ss 8.0	27142008
eCl@ss 9.0	27142008

## Fuse set - FUSE/TE5/2A/F-5PCS - 2906444

### Classifications

#### ETIM

ETIM 3.0	EC002298
ETIM 4.0	EC002298
ETIM 5.0	EC002298
ETIM 6.0	EC002298
ETIM 7.0	EC002298

#### UNSPSC

UNSPSC 13.2	39121622
UNSPSC 18.0	39121622
UNSPSC 19.0	39121622
UNSPSC 20.0	39121622
UNSPSC 21.0	39121622

### Approvals

#### Approvals

---

Approvals


EAC

---

Ex Approvals

---

#### Approval details

EAC		RU C- DE.BL08.B.00724
-----	---	--------------------------

Phoenix Contact 2020 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>