

Passive module - UM 45-FLK50/AB-1756 - 2968357


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



VARIOFACE COMPACT LINE, interface module for Allen-Bradley ControlLogix, with ControlLogix-specific labeling



Key Commercial Data

| | |
|--------------|---|
| Packing unit | 1 pc |
| GTIN |  4 017918 587772 |
| GTIN | 4017918587772 |

Technical data

Dimensions

| | |
|--------|--------|
| Width | 116 mm |
| Height | 45 mm |
| Depth | 50 mm |

Ambient conditions

| | |
|---|------------------|
| Ambient temperature (operation) | -20 °C ... 50 °C |
| Ambient temperature (storage/transport) | -20 °C ... 70 °C |

General

| | |
|--|----------------------|
| Max. perm. operating voltage | < 50 V AC 60 V DC |
| Max. perm. current (per branch) | 1 A |
| Max. permissible current (separate power supply) | 2 A (/Byte) |
| Mounting position | any |
| Degree of protection | IP00 |

Connection data for connection 1

| | |
|-------------------|------------------|
| Connection name | Field level |
| Connection method | Screw connection |

Passive module - UM 45-FLK50/AB-1756 - 2968357

Technical data

Connection data for connection 1

| | |
|----------------------------------|--|
| Stripping length | 6 mm |
| Screw thread | M3 |
| Conductor cross section solid | 0.14 mm ² ... 1.5 mm ² |
| Conductor cross section flexible | 0.14 mm ² ... 1.5 mm ² |
| Conductor cross section AWG | 26 ... 14 |

Standards and Regulations

| | |
|--------------------------|-----------------------|
| Standards/regulations | IEC 60664 |
| | DIN EN 50178 |
| Rated insulation voltage | 63 V |
| Rated surge voltage | 0.6 kV |
| Insulation | Functional insulation |
| Degree of pollution | 2 |
| Overvoltage category | II |

Environmental Product Compliance

| | |
|------------|---|
| REACH SVHC | Lead 7439-92-1 |
| China RoHS | Environmentally Friendly Use Period = 50 |
| | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

| | | |
|-----|--|--------------------------|
| EAC | | RU C- DE.A*30.B.01742 |
|-----|--|--------------------------|

Phoenix Contact 2019 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>