

LAMINATED TRANSFORMERS

Type UI30 / 10.5 - 6VA



AGENCY APPROVALS    

1. UL 506, File E113449


3. EN61558

Primary (V)	Secondary (V / mA)	No-Load Voltage (V)	Part Number	Agency Approvals
2x115	6/500 / 6/500	8.50/8.50	030-7004.0	1/3*
2x115	9/333 / 9/333	12.70/12.70	030-7007.0	1/3*
2x115	12/250 / 12/250	16.30/16.30	030-7010.0	1/3*
2x115	15/200 / 15/200	20.30/20.30	030-7013.0	1/3*
2x115	18/166 / 18/166	24.30/24.30	030-7016.0	1/3*
2x115	21/142 / 21/142	28.30/28.30	030-7019.0	1

***NOTE:** When checking the approval status of this product with VDE, add the prefix "BV" and the suffix "L" to the orderable Part Number (these letters will also be found on the part label). The prefix and suffix are not part of the orderable Part Number.

- ⊕ Frequency 50/60Hz
- ⊕ Weight: 0.175kg
- ⊕ Potted under vacuum
- ⊕ Packaging unit: 21 pieces
- ⊕ Split-bobbin
- ⊕ Fixing material for □ 2,5mm (0.098 inch)
- ⊕ Temperature class ta 40°C/B
- Self-tapping screws: DIN 7513 (M 3x8)
- ⊕ Non-short-circuit-proof
- Sheet-metal screws: DIN 7971 (2,9x6,5)

Mechanical



Schematics

