


(2,54mm) .100"

**BBS, BBL, BHS, BBD, BDL SERIES**

# MACHINED BOARD STACKING STRIPS

**Mates with:**  
SS, SD, HSS, SL, SDL,  
ESS, ESD

## FEATURES

- Low profile design achieves (3,89mm) .153" board spacings when mated with SL series.
- Choice of precision machined (BXX Series) or coined (LBS Series) terminals.
- Approach the reliability of a permanent connection with the flexibility of a separable connection.

## SPECIFICATIONS

For complete specifications see [www.samtec.com?BBS](http://www.samtec.com?BBS),  
[www.samtec.com?BBD](http://www.samtec.com?BBD),  
[www.samtec.com?BBL](http://www.samtec.com?BBL) or  
[www.samtec.com?BDL](http://www.samtec.com?BDL)

**BBS, BBD, BBL, BDL**



**Insulator Material:**

Black Glass Filled Polyester (BBS, BBD, BBL)

Black High Temp Nylon (BDL)

**Temperature Range:**

-55°C to +125°C

**Terminal Material:**

Phosphor Bronze or Brass

**Plating:**

Au or Sn over 50µ" (1,27µm) Ni

**Current Rating:**

1A

**RoHS Compliant:**

Yes

**Lead-Free Solderable:**

Wave only

## SPECIFICATIONS

For complete specifications see [www.samtec.com?BBS](http://www.samtec.com?BBS)

**BBS**

Same as BBS

except:

**Insulator Material:**

Black Liquid Crystal Polymer

**RoHS Compliant:**


Yes

**Lead-Free Solderable:**

Wave, or reflow with all Au



**Note:** Some lengths, styles and options are non-standard, non-returnable.



Due to technical progress, all designs, specifications and components are subject to change without notice.

[WWW.SAMTEC.COM](http://WWW.SAMTEC.COM)