

Automotive 2-line ESD protection for high speed lines

Datasheet - production data





Figure 1. Functional diagram (top view)



Features

- Flow-through routing to keep signal integrity
- Ultralarge bandwidth: 6 GHz
- Ultralow capacitance: 0.6 pF
- Low leakage current: 100 nA at 25 °C
- Extended operating junction temperature range: -40 °C to 150 °C
- RoHS compliant
- AEC-Q101 qualified

Benefits

- High ESD robustness of the equipment
- Suitable for high density boards

Complies with following standards:

- ISO 10605 - C = 150 pF, R = 330 Ω
 - 30 kV (air discharge)
 - 15 kV (contact discharge)
- ISO 10605 - C = 330 pF, R = 330 Ω
 - 30 kV (air discharge)
 - 15 kV (contact discharge)
- ISO 7637-3:
 - Pulse 3a: Vs = -150 V
 - Pulse 3b: Vs = +100 V

Applications

The HSP061-2Y is designed to protect against electrostatic discharge on automotive circuits driving:

- HDMI 1.3 and 1.4
- Ethernet
- Digital Video Interface
- Display Port
- USB 3.0
- Serial ATA
- High speed communication buses
- HMI

Description

The HSP061-2Y is a 2-channel ESD array with a rail to rail architecture designed specifically for the protection of high speed differential lines.

The ultralow variation of the capacitance ensures very low influence on signal-skew. The large bandwidth makes it compatible with 5 Gbps.

1 Characteristics

Table 1. Absolute maximum ratings $T_{amb} = 25\text{ }^{\circ}\text{C}$

| Symbol | Parameter | | Value | Unit |
|-------------------|---|--|-------------|--------------------|
| $V_{PP}^{(1)}$ | Peak pulse voltage | ISO 10605 - C = 150 pF, R = 330 Ω | | |
| | | contact discharge | 15 | kV |
| | | air discharge | 30 | |
| | | ISO 10605 - C = 330 pF, R = 330 Ω | | |
| contact discharge | 15 | | | |
| | | air discharge | 30 | |
| I_{pp} | Peak pulse current (8/20 μs) | | 3 | A |
| T_j | Operating junction temperature range | | -40 to +150 | $^{\circ}\text{C}$ |
| T_{stg} | Storage temperature range | | -65 to +150 | $^{\circ}\text{C}$ |
| T_L | Maximum lead solder temperature (10 s duration) | | 260 | $^{\circ}\text{C}$ |

1. For a surge greater than the maximum values, the diode will fail in short-circuit.

Table 2. Electrical characteristics $T_{amb} = 25\text{ }^{\circ}\text{C}$

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|------------------------|--|--|------|------|------|------|
| V_{BR} | Breakdown voltage | $I_R = 1\text{ mA}$ | 6 | | | V |
| I_R | Leakage current | $V_R = 5\text{ V}$ | | | 150 | nA |
| | | $V_R = 3\text{ V}$ | | | 100 | |
| V_{CL} | Clamping voltage | ISO 10605 - C = 150 pF, R = 330 Ω +8 kV contact discharge, measured at 30 ns | | 18 | | V |
| $C_{I/O - GND}$ | Capacitance (input/output to ground) | $V_{I/O} = 0\text{ V}$, F = 200 to 3000 MHz, $V_{OSC} = 30\text{ mV}$ | | 0.6 | 0.85 | pF |
| $\Delta C_{I/O - GND}$ | Capacitance variation (input/output to ground) | $V_{I/O} = 0\text{ V}$ F = 200 to 3000 MHz, $V_{OSC} = 30\text{ mV}$ | | 0.03 | 0.08 | pF |
| f_C | Cut-off frequency | -3 dB | | 5.5 | | GHz |

Figure 2. Leakage current versus junction temperature (typical values)




Figure 3. S21 attenuation measurement




Figure 4. Eye diagram - HDMI mask at 3.4 Gbps per channel⁽¹⁾






Figure 5. ESD response to IEC 61000-4-2 (+8 kV contact discharge)



1. HDMI specification conditions. This information can be provided for other applications. Please contact your local ST office.

Figure 6. ESD response to IEC 61000-4-2 (-8 kV contact discharge)



2 Application information

More information is available in the STMicroelectronics application note:

AN2689, "Protection of automotive electronics from electrical hazards, guidelines for design and component selection".

3 Package information

- Epoxy meets UL94, V0
- Lead-free packages

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK[®] packages, depending on their level of environmental compliance. ECOPACK[®] specifications, grade definitions and product status are available at: www.st.com. ECOPACK[®] is an ST trademark.

Figure 7. SOT666 dimension definitions




Table 3. SOT666 dimension values

| Ref. | Dimensions | | | | | |
|------|-------------|------|------|--------|-------|-------|
| | Millimeters | | | Inches | | |
| | Min. | Typ. | Max. | Min. | Typ. | Max. |
| A | 0.45 | | 0.60 | 0.018 | | 0.024 |
| A3 | 0.08 | | 0.18 | 0.003 | | 0.007 |
| b | 0.17 | | 0.34 | 0.007 | | 0.013 |
| b1 | 0.19 | 0.27 | 0.34 | 0.007 | 0.011 | 0.013 |
| D | 1.50 | | 1.70 | 0.059 | | 0.067 |
| E | 1.50 | | 1.70 | 0.059 | | 0.067 |
| E1 | 1.10 | | 1.30 | 0.043 | | 0.051 |
| e | | 0.50 | | | 0.020 | |
| L1 | | 0.19 | | | 0.007 | |
| L2 | 0.10 | | 0.30 | 0.004 | | 0.012 |
| L3 | | 0.10 | | | 0.004 | |

Figure 8. Footprint recommendations dimensions in mm (inches)





Figure 9. Marking



Note: Product marking may be rotated by 90° or 180° to differentiate assembly location. In no case should this product marking be used to orient the component for its placement on a PCB. Only pin 1 mark is to be used for this purpose.

4 Ordering information

Figure 10. Ordering information scheme




Table 4. Ordering information

| Order code | Marking | Package | Weight | Base qty | Delivery mode |
|-------------|-------------------|---------|---------|----------|---------------|
| HSP061-2P6Y | RY ⁽¹⁾ | SOT-666 | 2.85 mg | 3000 | Tape and reel |

1. The marking can be rotated by 90° or 180° to differentiate assembly location

5 Revision history

Table 5. Document revision history

| Date | Revision | Changes |
|-------------|----------|------------------|
| 17-Oct-2013 | 1 | Initial release. |

Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

ST PRODUCTS ARE NOT DESIGNED OR AUTHORIZED FOR USE IN: (A) SAFETY CRITICAL APPLICATIONS SUCH AS LIFE SUPPORTING, ACTIVE IMPLANTED DEVICES OR SYSTEMS WITH PRODUCT FUNCTIONAL SAFETY REQUIREMENTS; (B) AERONAUTIC APPLICATIONS; (C) AUTOMOTIVE APPLICATIONS OR ENVIRONMENTS, AND/OR (D) AEROSPACE APPLICATIONS OR ENVIRONMENTS. WHERE ST PRODUCTS ARE NOT DESIGNED FOR SUCH USE, THE PURCHASER SHALL USE PRODUCTS AT PURCHASER'S SOLE RISK, EVEN IF ST HAS BEEN INFORMED IN WRITING OF SUCH USAGE, UNLESS A PRODUCT IS EXPRESSLY DESIGNATED BY ST AS BEING INTENDED FOR "AUTOMOTIVE, AUTOMOTIVE SAFETY OR MEDICAL" INDUSTRY DOMAINS ACCORDING TO ST PRODUCT DESIGN SPECIFICATIONS. PRODUCTS FORMALLY ESCC, QML OR JAN QUALIFIED ARE DEEMED SUITABLE FOR USE IN AEROSPACE BY THE CORRESPONDING GOVERNMENTAL AGENCY.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2013 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Philippines - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com