



**Tripp Lite**  
 1111 West 35th Street  
 Chicago, IL 60609 USA  
 Telephone: +(773) 869 1234  
 E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: PDUH20DV

**Single-Phase Basic PDU, 20A 100-240V, 1U Horizontal Rackmount, C19 & C13 outlets, C20 inlet, C20 line cord and L6-20P adapter**

### Highlights

- Basic single phase 20A 100-240V PDU
- 1U horizontal rackmount installation
- C20 input with NEMA L6-20P adapter; 12 ft. / 3.7m line cord
- 2 C19 and 12 C13 outlets
- Reversible housing; 3.75 in. / 9.5cm depth



### Description

Tripp Lite Basic Power Distribution Units / PDU systems offer reliable rackmount power distribution. Supplies equipment with continuous power from any protected UPS, generator or mains input power source. High quality design includes rugged all-metal housing and secure rackmount installation with included mounting accessories.

#### Applications

- Ideal for datacenters, network closets, equipment racks and a wide variety of other application types

#### Package Includes

- PDUH20DV PDU rackmount PDU
- Owner's manual

### Features

- 20A single phase 100-240V Basic Power Distribution Unit / PDU
- C20 inlet with included C19 to C20 input cable and L6-20P adapter
- 14 outlets (2 C19, 12 C13)
- 12 ft. / 3.7m line cord
- 1U horizontal rackmount format installs in one rack space
- Mounting flanges support installation in 2 and 4 post racks, with additional support for wall-mount and under-counter installation formats
- Reversible housing
- Back panel grounding lug

### Specifications

OVERVIEW	
Model Type	Basic
PDU Type	Basic
OUTPUT	
Frequency compatibility	50 / 60 Hz

<b>Output nominal voltage</b>	100-240V
<b>Overload protection</b>	n/a
<b>Outlet quantity / type</b>	2 C19, 12 C13
<b>Outlet Type</b>	IEC-C13, IEC-C19
<b>INPUT</b>	
<b>PDU Input Voltage</b>	100; 120; 127; 200; 208; 230; 240
<b>Maximum Input Amps (A)</b>	20
<b>PDU Plug Type</b>	NEMA L6-20P; IEC-320 C20
<b>Input cord length (ft.)</b>	12
<b>Input cord length (m)</b>	3.7
<b>Input cord details</b>	Input cable is detachable PDU C20 inlet
<b>Voltage compatibility (VAC)</b>	100; 120; 127; 200; 208; 230; 240
<b>Phase</b>	Single-Phase
<b>PHYSICAL</b>	
<b>Shipping weight (lbs)</b>	5.7
<b>Shipping weight (kg)</b>	2.6
<b>Unit Dimensions (HWD/in)</b>	1.75 (1U) x 17.25 x 3.75
<b>Unit Dimensions (HWD/cm)</b>	4.45 x 43.8 x 9.5
<b>Shipping Dimensions (HWD/in)</b>	2.25 x 20.5 x 9.5
<b>Shipping Dimensions (HWD/cm)</b>	5.7 x 52.1 x 24.1
<b>Unit weight (lbs)</b>	3.75
<b>Unit weight (kg)</b>	1.7
<b>Material of construction</b>	Sheet metal
<b>Style</b>	Rackmount, Vertical Rackmount, Wallmount/Under-Counter
<b>Form factors supported</b>	1U rackmount, 0U vertical rackmount, wall-mount, and under-counter installation
<b>PDU Form Factor</b>	Horizontal (1U, 2U, etc)
<b>Outlets center to center measurement</b>	Distance between front (C13) outlets = 28.75mm; Distance between rear (C19) outlets = 55mm; Distance between rear (C13) outlets = 28.75mm
<b>SPECIAL FEATURES</b>	
<b>Appearance</b>	All black color scheme
<b>TVSS grounding</b>	Rear grounding lug
<b>CERTIFICATIONS</b>	
<b>Certifications</b>	Tested to UL 60950 (USA), CSA (Canada), CE (EU), RoHS Compliant
<b>WARRANTY</b>	

**Product Warranty Period  
(Worldwide)**

Lifetime limited warranty

## Related Items

### Optional Products

Product Type	Related Model	Description	Qty.
Power Cables	<a href="#">P002-002</a>	2-ft. Power Cord (IEC-320-C14 to NEMA 5-15R)	1
Power Cables	<a href="#">P005-002</a>	2-ft. Heavy-Duty 14AWG Power cord ( IEC-320-C13 to IEC-320-C14)	1
Power Cables	<a href="#">P005-006</a>	6-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to IEC-320-C14)	1
Power Cables	<a href="#">P005-010</a>	10-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to IEC-320-C14)	1
Power Cables	<a href="#">P032-007</a>	7-ft. 12AWG Heavy Duty Power cord ( IEC-320- C13 to IEC-320-C20)	1
Power Cables	<a href="#">P034-010</a>	10-ft. 14AWG Heavy Duty Power cord ( IEC-320-C19 to NEMA 5-15P)	1
Power Cables	<a href="#">P036-002</a>	2-ft. 12AWG Heavy Duty Power cord (IEC-320-C19 to IEC-320-C20)	1
Power Cables	<a href="#">P036-006</a>	6-ft. 12AWG Heavy Duty Power cord (IEC-320-C19 to IEC-320-C20)	1
Power Cables	<a href="#">P040-010</a>	10-ft. 12AWG Heavy Duty Power cord (IEC-320-C19 to IEC-320-L6-20P)	1
Power Cables	<a href="#">P045-010</a>	10-ft. 12AWG Heavy-Duty Power cord (IEC-320-C19 to NEMA L5-20P)	1
Power Cables	<a href="#">P047-002</a>	2-ft. 14AWG Heavy Duty Power cord (IEC-320-C19 to IEC-320-C14)	1
Power Cables	<a href="#">P047-004</a>	4-ft. 14AWG Heavy Duty Power cord (IEC-320-C19 to IEC-320-C14)	1
Power Cables	<a href="#">P047-006</a>	6-ft. 14AWG Heavy Duty Power cord (IEC-320-C19 to IEC-320-C14)	1
Power Cables	<a href="#">P047-010</a>	10-ft. 14AWG Heavy Duty Power cord (IEC-320-C19 to IEC-320-C14)	1
Power Cables	<a href="#">P049-010</a>	10-ft. 12AWG Heavy Duty Power cord (IEC-320-C19 to NEMA 5-20P)	1
Power Cables	<a href="#">P050-008</a>	8-ft. Power cord (IEC-320-C19 to CEE 7/7 SCHUKO)	1
Power Cables	<a href="#">P052-008</a>	8-ft. Power cord (IEC-320-C19 to BS1363 UK Plug)	1
Power Cables	<a href="#">P070-010</a>	10-ft. IEC309 to C19 Power Cord	1
Rack Accessories	<a href="#">PDU5IDEBRKT</a>	Enables Vertical Installation of Select 1U PDUs, Power Strips and Surge Suppressors in SmartRack Configurations	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=4799](http://www.tripplite.com/en/products/model.cfm?txtModelID=4799).

Copyright © 2012 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.