

## 7-outlet, 12-ft cord, 1080 joule - Protect It! Surge Suppressor

MODEL NUMBER: TLP712



### Highlights

- 7 outlets / 12-ft. cord
- 1080 joule rating
- \$25,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only)

### Applications

- Ideal for any desktop, network or home computing application requiring AC protection

### Package Includes

- TLP712 Surge Suppressor
- Instruction manual and warranty information

### Description

Tripp Lite's TLP712 surge suppressor offers economical AC surge suppression for protection of workstations, desktop PCs, telecom systems and other sensitive electronics. AC surge suppression shields connected equipment from damage and performance problems due to transient surges. TLP712 offers 7 total outlets, 12 foot cord and diagnostic LED to confirm surge suppression is present. AC suppression rated at 1080 joules shields equipment from surges and line noise. Attractive light gray suppressor housing with keyhole mounting slots and 1 designated transformer plug outlet offer convenient protection of desktop computer equipment and accessories. \$25,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

PLUG/OUTLETS: Input: NEMA5-15P/Output: 7 NEMA5-15R/12 ft. AC line cord

ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires NEMA5-15R wall receptacle)

FORMAT: Corded multi-outlet strip with 1 transformer spaced outlet

SUPPRESSION: AC: 150V RMS Clamping/1080 joules/400V UL1449 3rd Edition Let-through Rating

### Features

- 7 outlets / 12-ft cord
- Surge suppression rating: 1080 joules
- EMI/RFI noise filtering
- Can accommodate 1 transformer without blocking remaining outlets
- Diagnostic LEDs indicate protection present & ground present
- Keyhole supports for wall mounting
- \$25,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only) covers connected equipment

## Specifications



| <b>OVERVIEW</b>                    |  |
|------------------------------------|--|
| Intended Application               | Home/Office  |
| Style                              | Strip  |
| <b>OUTPUT</b>                      |  |
| Frequency Compatibility            | 50 / 60 Hz   |
| Output (Watts)                     | 1800   |
| Circuit Breaker (amps)             | 15   |
| Outlet Quantity / Type             | 7 NEMA 5-15R   |
| Number of Outlets                  | 7  |
| Transformer Accommodation          | Supports 1 large transformer plug accessory without covering remaining outlets, accepts up to 4 transformers total |
| Outlet Orientation                 | Single row   |
| <b>INPUT</b>                       |  |
| Nominal Input Voltage(s) Supported | 120V AC  |
| Recommended Electrical Service     | 120V (110-125V)  |
| Input Connection Type              | NEMA 5-15P   |
| Input Cord Length (ft.)            | 12   |
| Input Cord Length (m)              | 3.66   |
| Input Cord Gauge Type              | 14 gauge, SJT  |
| Voltage Compatibility (VAC)        | 120  |
| Maximum Surge Amps                 | 72000  |
| <b>LEDS ALARMS &amp; SWITCHES</b>  |  |
| Switches                           | Combination AC circuit breaker and 2 position red illuminated on/off power switch                                  |
| Diagnostic LEDs                    | Built-in LED confirms suppressor "protection present" (green) status   |
| <b>SURGE / NOISE SUPPRESSION</b>   |  |
| AC Suppression Joule Rating        | 1080   |
| AC Suppression Response Time       | < 1 ns   |
| Protection Modes                   | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression                                 |
| Clamping Voltage (RMS)             | 150  |
| UL1449 Let Through Rating          | 400V   |
| EMI / RFI Filtering                | Up to 20 dB  |
| <b>DATALINE SURGE SUPPRESSION</b>  |  |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

|  |   |
|--|---|
| Cable (Coax) Protection                                    | No  |
| Network (Ethernet) Protection                              | No  |
| <b>PHYSICAL</b>  |   |
| Shipping Dimensions (hwd / in.)                            | 13.78 x 4.92 x 2.36   |
| Shipping Dimensions (hwd / cm)                             | 35.00 x 12.50 x 5.99  |
| Shipping Weight (lbs.)                                     | 1.92  |
| Shipping Weight (kg)                                       | 0.87  |
| Unit Dimensions (hwd / in.)                                | 1.32 x 2.05 x 11.69   |
| Unit Dimensions (hwd / cm)                                 | 3.35 x 5.21 x 29.69   |
| Unit Weight (lbs.)   | 1.76  |
| Unit Weight (kg)   | 0.80  |
| Material of Construction                                   | Plastic   |
| Integrated Keyhole Mounting Tabs                           | Keyhole mounting slots enable wall mounting   |
| Housing Color  | Light Gray  |
| Receptacle Color   | Light Gray  |
| Color (AC Line Cord)                                       | Light Gray  |
| Outlets Measurement (Center to Center)                     | Distance between standard outlets = 29mm; Distance between last standard outlet and transformer outlet = 33mm |
| Keyhole Slot Mounting Measurement (Center to Center)       | Distance between slots = 151mm; Distance between slot height = 24mm   |
| <b>CERTIFICATIONS</b>                                      |   |
| UL1449 3rd Edition (AC Suppression)                        | UL1449 3rd EDITION  |
| NOM (Mexico)   | NOM   |
| UL1363 (Power Tap)   | UL1363  |
| cUL / CSA (Canada)   | cUL   |
| Approvals  | Exceeds IEEE 587 category A&B specifications  |
| <b>WARRANTY</b>  |   |
| Product Warranty Period (Worldwide)                        | Lifetime limited warranty   |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$25,000 <a href="#">Ultimate Lifetime Insurance</a>  |

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.