

**Cable glands
VG 13,5-MS68**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



Screwed joints that comply with the high demands of class of protection IP 68

General ordering data

Order No.	1569090000
Type	VG 13,5-MS68
Version	Cable gland, Brass, nickel-plated, External thread: PG 13.5
GTIN (EAN)	4008190177089
Qty.	50 pc(s).

**Cable glands
VG 13,5-MS68**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Length	31 mm	Net weight	28.5 g
--------	-------	------------	--------

General information

AF size 1	22 mm	AF size 2	22 mm
Cable gland	PG	Clamp insert	Polyamide
Clamping range, max.	12 mm	Clamping range, min.	6 mm
External thread	PG 13.5	Length of thread	6.5 mm
Material	Brass, nickel-plated	O-Ring	NBR
Operating temperature range, max.	100 °C	Operating temperature range, min.	-40 °C
Protection degree with GWDR	IP 68 - 5 bar, IP 69K	Seal insert	CR
Sealing	NBR	Torque for cap nut, max.	9 Nm
Torque for cap nut, min.	7 Nm	Torque for connecting adapter, max.	6.5 Nm
Torque for connecting adapter, min.	4.5 Nm		

Classifications

ETIM 2.0	EC000441	ETIM 3.0	EC000441
UNSPSC	30-21-18-01	eClass 4.1	27-14-12-09
eClass 5.1	27-14-91-09	eClass 6.2	27-14-91-09
eClass 7.1	27-14-91-09		

Approvals

Approvals



ROHS Conform