



Specifications

CONTACT RATING:0.1A 30 VDC
 MECHANICAL ELECTRICAL LIFE:50,000 cycles
 CONTACT RESISTANCE:150Ωmax. initial
 INSULATION RESISTANCE:100Ωmin. 100VDC
 OPERATING TEMPERATURE:-20℃to+70℃
 DIELECTRIC STRENGTH:100 volts AC 60 HZ
 PACKAGING: Bulk

ITEM	PART NAME	TER,NO	QTY	MATERIAL	FINISHING	REMARK
⑥	Spring	—	1	Sus	Natural	
⑤	Contact Spring	—	1	Phosphor Bronze	Plating silver	
④	Terminal	—	2	Phosphor Bronze	Plating silver	
③	Base	—	1	Nylon		
②	Cover	—	1	Nylon		
①	Keystake	—	1	Nylon		

广东星坤科技股份有限公司

MARK	DATE	DESCRIPTION
ΔX		
ΔX		
ΔX		

文件工程章

REVISIONS	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES

ANGLAR ±5°
 L ≤ 4 ±0.2
 4 < L ≤ 16 ±0.3
 16 < L ≤ 63 ±0.4
 L > 63 ±0.5

XKIB

XKB INDUSTRIAL PRECISION CO., LIMITED

DSND	SCALE: N/A	MODEL TYPE: DETECT SWITCH
DWN	VIEW:	PART NO.: TM-W-09
CHKD	UNIT: mm/in	DWG NO.:
APPD	SIZE: A4	
	WEIGHT	SHEET 1/1
		REVISIC A0