


This item includes:

 <p><b>Item No.: 221-412</b> Splicing connector with levers; for all conductor types; max. 4 mm<sup>2</sup>; 2-conductor; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm<sup>2</sup>; transparent</p>	 <p><b>Item No.: 221-413</b> Splicing connector with levers; for all conductor types; max. 4 mm<sup>2</sup>; 3-conductor; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm<sup>2</sup>; transparent</p>	 <p><b>Item No.: 221-415</b> Splicing connector with levers; for all conductor types; max. 4 mm<sup>2</sup>; 5-conductor; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm<sup>2</sup>; transparent</p>	 <p><b>Item No.: 221-500</b> <span style="float: right;">2</span> Mounting carrier; 221 Series - 4 mm<sup>2</sup>; for DIN-35 rail mounting/screw mounting; orange</p>
 <p><b>Item No.: 221-2401</b> Inline splicing connector with levers; for all conductor types; max. 4 mm<sup>2</sup>; 2-conductor; transparent housing; white cover; Surrounding air temperature: max 85°C (T85); 4,00 mm<sup>2</sup>; transparent</p>	 <p><b>Item No.: 221-2503</b> <span style="float: right;">1</span> Mounting carrier with strain relief; 3-way; for inline splicing connector with lever; for screw mounting; gray</p>	 <p><b>Item No.: 221-2502</b> <span style="float: right;">1</span> Mounting carrier with strain relief; 2-way; for inline splicing connector with lever; for screw mounting; gray</p>	

Notes

General safety instructions

**NOTICE: Observe installation and safety instructions!**

- **Only to be used by electricians!**
- Do not work under voltage/load!
- Use only for proper use!
- Observe national regulations/standards/guidelines!
- Observe technical specifications for the products!
- Observe the number of permissible potentials!
- Do not use damaged/dirty components!
- Observe conductor types, cross-sections and strip lengths!
- Insert conductor until it hits the product's backstop!
- Use original accessories!

**To be sold only with installation instructions!**

Physical data

Width	259 mm / 10.197 inches
Height	63 mm / 2.48 inches
Depth	155 mm / 6.102 inches

Material data

Note (material data)	<a href="#">Information on material specifications can be found here</a>
Fire load	16.104 MJ
Weight	899 g



**Commercial data**

PU (SPU)	1 pcs
Packaging type	Box
Country of origin	QU
GTIN	4066966405002
Customs tariff number	85369010000

**Product classification**

UNSPSC	24112401
ECCN	NO US CLASSIFICATION

**Environmental Product Compliance**

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------