


SMD 1202 MHZ SAW FILTER



AFII-SW-0058

Request Samples



Check Inventory



1.4 x 1.1 x 0.7mm
RoHS Compliant
MSL Level = 3



Features

- Supports GNSS L2/G3/L3OC/E5a/E5b/B2a/B2b Band
- 1.4 x 1.1 x 0.7mm in Size
- Low Insertion Loss: 1.8 dB
- Out-of-Band Rejection: > 28 dB
- Maximum Input Power: +10 dBm


Applications

- High-Precision GNSS Modules
- RTK Systems
- Automotive Transportation & Telematics
- Asset Tracking / Fleet Management
- UAVs, Robotics & Autonomous Vehicles
- Micro-Mobility Solutions
- Precision Agriculture

Product Image



SMD 1202 MHZ SAW FILTER



AFII-SW-0058

Request Samples



Check Inventory



1.4 x 1.1 x 0.7mm
RoHS Compliant
MSL Level = 3

Electrical Specification

Parameters	Minimum	Typical	Maximum	Units	Notes
Center Frequency(f_c)	-	1202	-	MHz	-
VSWR	-	1.5	2.0		1166 ~ 1238MHz
Insertion Loss ⁽¹⁾	-	1.8	2.3	dB	1166 ~ 1238MHz
Amplitude Ripple	-	1.2	2.1		1166 ~ 1238MHz
Group Delay	-	12.8	38.0	ns	1166 ~ 1238MHz
Group Delay Ripple	-	0.19	0.86	ns	1166 ~ 1238MHz
Attenuation (Reference level from 0 dB) Amplitude Ripple ⁽¹⁾	28	34	-	dB	100 ~1106 MHz
	30	38	-		1106 ~1136 MHz
	14	28	-		1268 ~1318 MHz
	25	32	-		1318 ~1800 MHz
	30	40	-		1800 ~2000 MHz
	30	35	-		2400 ~2500 MHz
Source Impedance ⁽³⁾ (single ended)	-	50	-	Ω	-
Load Impedance ⁽³⁾ (single ended)	-	50	-	Ω	-
RF Power Dissipation	-	10	-	dBm	

Notes: (1) Averaged values of linear S-Parameters at +25°C

(2) Averaged values of linear S-Parameters at +25°C

(3) A matching network is necessary (refer to the Measurement Circuits section).

Mechanical Specification

Parameters	Specifications
Filter Dimension	1.4 x 1.1 x 0.7mm
Mounting Type	Surface Mount

Environmental Specification

Parameters	Specifications
Operating Temperature Range	-40°C ~ +85°C
Storage Temperature Range	-40°C ~ +85°C
ESD (HBM)	>100 V
ESD (CDM)	>100 V
MSL level	3
RoHS Compliant	Yes




5101 Hidden Creek Ln Spicewood TX 78669
 Phone: 512-371-6159 | Fax: 512-351-8858
 For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 03-13-25

ABRACON IS
 ISO9001-2015
 CERTIFIED

SMD 1202 MHZ SAW FILTER



AFII-SW-0058

Request Samples



Check Inventory




1.4 x 1.1 x 0.7mm
RoHS Compliant
MSL Level = 3

Ordering Information

Part Number	Description
AFII-SW-0058	SMD 1202 MHZ SAW FILTER on Cut Tape
AFII-SW-0058-T	SMD 1202 MHZ SAW FILTER on Tape & Reel
AFII-SW-0058-EVB	SMD 1202 MHZ SAW FILTER Evaluation Board

Note: Other options not listed may be available upon request via [Abracon online support](#)

SMD 1202 MHZ SAW FILTER



AFII-SW-0058

Request Samples




Check Inventory




1.4 x 1.1 x 0.7mm
RoHS Compliant
MSL Level = 3


Product Dimensions



TOP VIEW



FRONT VIEW




BOTTOM VIEW

Unit : mm

Pin No.	Description
1	Input
4	Output
2, 3, 5	Ground

SMD 1202 MHZ SAW FILTER



AFII-SW-0058

Request Samples




Check Inventory



1.4 x 1.1 x 0.7mm
RoHS Compliant
MSL Level = 3

Recommended Land Pattern




Land Pattern

Unit : mm

Please note: The line width should be designed to achieve a 50-ohm characteristic impedance, depending on the PCB material and thickness. For technical assistance, please contact [Abracon online support](#) through our online support platform.

SMD 1202 MHZ SAW FILTER



AFII-SW-0058

Request Samples




Check Inventory




1.4 x 1.1 x 0.7mm
RoHS Compliant
MSL Level = 3

Measurement Circuit



Port	Matching Component
Input (Pin 1)	L1: 8.2 nH
Output (Pin 4)	L2: 8.2 nH

SMD 1202 MHZ SAW FILTER



AFII-SW-0058

Request Samples





Check Inventory




1.4 x 1.1 x 0.7mm
RoHS Compliant
MSL Level = 3

Frequency Characteristics

S21 narrow band



SMD 1202 MHZ SAW FILTER



AFII-SW-0058

Request Samples




Check Inventory




1.4 x 1.1 x 0.7mm
RoHS Compliant
MSL Level = 3


S21 Wide Band



Group Delay



SMD 1202 MHZ SAW FILTER



AFII-SW-0058

Request Samples





Check Inventory




1.4 x 1.1 x 0.7mm
RoHS Compliant
MSL Level = 3

VSWR (S11 & S22)



SMD 1202 MHZ SAW FILTER



AFII-SW-0058

Request Samples




Check Inventory




1.4 x 1.1 x 0.7mm
RoHS Compliant
MSL Level = 3

Smith Chart (S11 & S22)


Smith chart S11 (1166~1238MHz)



Smith chart S22 (1166~1238MHz)



SMD 1202 MHZ SAW FILTER



AFII-SW-0058

Request Samples



Check Inventory



1.4 x 1.1 x 0.7mm
RoHS Compliant
MSL Level = 3

Reflow Profile [JEDEC J-STD-020]




Table 1

SnPb Eutectic Process Classification Temperatures (T_c)		
Package Thickness	Volume mm^3 <350	Volume mm^3 \geq 350
<2.5mm	235°C	220°C
\geq 2.5mm	220°C	220°C

Table 2


Pb-Free Process Classification Temperatures (T_c)			
Package Thickness	Volume mm^3 <350	Volume mm^3 350-2000	Volume mm^3 >2000
<1.6mm	260°C	260°C	260°C
1.6mm - 2.5mm	260°C	250°C	245°C
>2.5mm	250°C	245°C	245°C

Profile Feature	Sn-Pb Eutectic Assembly	Pb-Free Assembly
Preheat / soak		
Temperature minimum (T_{smin})	100°C	150°C
Temperature maximum (T_{smax})	150°C	180°C
Time (T_{smin} to T_{smax}) (t_s)	60 – 120 sec.	60 – 90 sec.
Average ramp-up rate (T_{smax} to T_p)	3°C/sec. max	3°C/sec. max
Liquidous temperature (T_L)	183°C	220°C
Time at Liquidous (T_L)	60 – 150 sec.	50 – 80 sec.
Peak package body temperature (T_p)*	See Table 1	See Table 2
Time (T_p)** within 5°C of the specified classification temperature (T_c)	20 sec.	20 ~ 40 sec.
Ramp-down rate (T_p to T_{smax})	6°C/sec. max	6°C/sec. max
Time 25°C to peak temperature	6 min. max	8 min. max
Reflow cycles	2 max	2 max

*Tolerance for peak profile temperature (T_p) is defined as a supplier minimum and a user maximum.

**Tolerance for time at peak profile temperature (t_p) is defined as a supplier minimum and a user maximum.

SMD 1202 MHZ SAW FILTER



AFII-SW-0058

Request Samples




Check Inventory



1.4 x 1.1 x 0.7mm
RoHS Compliant
MSL Level = 3

Packaging

Tape & Reel Dimension



Unit: mm

Carrier Tape Specifications (mm)

Do	D ₁	E ₁	P ₀	P ₂	F	P ₁	W	A ₀	B ₀	K ₀	Reel Qty
1.55 ± 0.05	0.60 ± 0.05	1.75 ± 0.1	4.0 ± 0.1	2.0 ± 0.05	3.5 ± 0.05	4.0 ± 0.1	8.0 ± 0.1	1.30 ± 0.05	1.60 ± 0.05	0.77 ± 0.05	5,000

Reel Specifications (mm)

A	W ₁	N	C
178.0 ± 1.0	8.48 ± 0.15	57.12 ± 0.15	13.12 ± 0.15

ATTENTION: Abracon LLC's products are Commercial-Off-The-Shelf ('COTS'), which are designed, intended, and validated for use in commercial, industrial, and automotive applications. The customer is responsible for testing and verifying the performance of an Abracon solution to meet their system-level requirements.



5101 Hidden Creek Ln Spicewood TX 78669
 Phone: 512-371-6159 | Fax: 512-351-8858
 For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 03-13-25

ABRACON IS
 ISO9001-2015
 CERTIFIED