


AMBER-IP-2X6-T2

IESNA Type II (medium) beam applicable for European P-class standard pedestrian lighting and M-class roads

SPECIFICATION:

Dimensions	71.4 x 173.0
Height	9.2 mm
Fastening	screw
Ingress protection classes	IP67
ROHS compliant	yes ⓘ




MATERIALS:

Component	Type	Material	Colour	Finish	Length (mm)
AMBER-IP-2X6-T2	Multi-lens	PMMA	amber		
2X6-SEAL25	Seal	Silicone	white		

ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
CS19240_AMBER-IP-2X6-T2	Multi-lens	120	40	40	7.6
» Box size: 476 x 273 x 247 mm					





See also our general installation guide: www.ledil.com/installation_guide

OPTICAL RESULTS (MEASURED):





LED XP-G3
FWHM / FWTM Asymmetric
Efficiency 73 %
Peak intensity 0.7 cd/lm
LEDs/each optic 1
Light colour/type White
Amount of Blue light (380-500 nm) 0.3 %
CCT (LED/with lens)* 3780K/2187K
Required components:



*the measured CCT with lens doesn't follow the Black Body Locus line





LED LUXEON 5050 HE
FWHM / FWTM Asymmetric
Efficiency 73 %
Peak intensity 0.6 cd/lm
LEDs/each optic 1
Light colour/type White
Amount of Blue light (380-500 nm) 0.4 %
CCT (LED/with lens)* 3768K/2197K
Required components:



Light distribution files






LED LUXEON HL2X-D
FWHM / FWTM Asymmetric
Efficiency 74 %
Peak intensity 0.7 cd/lm
LEDs/each optic 1
Light colour/type White
Amount of Blue light (380-500 nm) 0.4 %
CCT (LED/with lens)* 3813K/2207K
Required components:



Light distribution files



OPTICAL RESULTS (MEASURED):



OPTICAL RESULTS (MEASURED):

OSRAM
Opto Semiconductors



LED OSLON Square CSSRM2/CSSRM3
 FWHM / FWTM Asymmetric
 Efficiency 74 %
 Peak intensity 0.8 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Amount of Blue light (380-500 nm) 0.4 %
 CCT (LED/with lens)* 3803K/2192K
 Required components:



Light distribution files

SAMSUNG



LED LH351C
 FWHM / FWTM Asymmetric
 Efficiency 74 %
 Peak intensity 0.8 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Amount of Blue light (380-500 nm) 0.4 %
 CCT (LED/with lens)* 3735K/2204K
 Required components:



Light distribution files



SAMSUNG

LED LH502D
 FWHM / FWTM Asymmetric
 Efficiency 74 %
 Peak intensity 0.6 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Amount of Blue light (380-500 nm) 0.4 %
 CCT (LED/with lens)* 3783K/2166K
 Required components:



Light distribution files

OPTICAL RESULTS (MEASURED):



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 7
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Poznan, Poland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Ledil:](#)

[CS19240_AMBER-IP-2X6-T2](#)