


THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ANDERSON POWER PRODUCTS. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF ANDERSON POWER PRODUCTS IS PROHIBITED.

Copyright 2021

ANDERSON POWER PRODUCTS RESERVES THE RIGHT TO ALTER PRODUCT TYPES, THEIR TECHNICAL DATA, DIMENSION, STYLE AND ACCESSORIES WITHOUT PRIOR NOTIFICATION.




CONNECTOR 1 [1]		CABLE		CONNECTOR 2 [1]	
TYPE	SAF-D-GRID® SERIES (3-5958P2)	TYPE	SJT/H05VV-F	TYPE	IEC 60320 C20
APPROVAL(S)	cURus TO UL 1977, FILE# E26226	APPROVAL(S)	UL/CSA/VDE/CCC/NSW [2]	APPROVAL(S)	UL, FIMKO, CCC, NSW [2]
INTERRUPT CURRENT	30A UL, CSA, IEC	CONDUCTOR SIZE / QTY.	12 AWG/2.5mm ² - 3 COND.	CURRENT	20A (UL) 16A (IEC)
DISCONNECT CURRENT	30A UL, CSA, 32A IEC	VOLTAGE RATING	300V	MAX VOLTAGE	250V
VOLTAGE	400V (HOT PLUG), 600V DISCONNECT	FLAMMABILITY / TEMP.	75°C [1]	MAX TEMP	70°C (PIN)
MAX TEMP	90°C	JACKET	PVC, O.D. 11.2 [.44] [1]	CONTACTS	Ni PLATED BRASS
CONTACTS	COPPER ALLOY, SILVER PLATED	JACKET COLOR [1]	RED OR BLUE	HOUSING	RED OR BLUE
HOUSING	POLYCARBONATE, BLACK			OVERMOLD	RED OR BLUE
OVERMOLD	PVC, BLACK				

PLUG COMPLIES WITH IEC 60320- C20 CONFIGURATION. VISUAL REPRESENTATION IS FOR REFERENCE ONLY.

PRODUCT NUMBERING AND LENGTHS			
PART NUMBER			
APP	COLOR	M	FT
2058KH1-RED-BK	RED	1	3.3
2058KH2-RED-BK	RED	2	6.6
2058KH3-RED-BK	RED	3	9.9
2058KH3R5-RED-BK	RED	3.5	11.5
2058KH4R5-RED-BK	RED	4.5	14.8
2058KH1-BLUE-BK	BLUE	1	3.3
2058KH2-BLUE-BK	BLUE	2	6.6
2058KH3-BLUE-BK	BLUE	3	9.9
2058KH3R5-BLUE-BK	BLUE	3.5	11.5
2058KH4R5-BLUE-BK	BLUE	4.5	14.8
2058KH5-RED-BK	RED	5	16.4
2058KH6-RED-BK	RED	6	19.7
2058KH5-BLUE-BK	BLUE	5	16.4
2058KH6-BLUE-BK	BLUE	6	19.7

OVERALL RATINGS AND SPECIFICATIONS	
MAX VOLTAGE	250V
MAX CURRENT	20A (UL), 16A (IEC)
TEMPERATURE	70°C

LABEL- EXAMPLE- SEE TABLE FOR ACTUAL TEXT



- NOTES:
- ASSEMBLIES TO BE 100% CHECKED FOR CONTINUITY, POLARITY AND DIELECTRIC WITHSTAND VOLTAGE AT 2,500 VAC FOR 3 SECONDS.
 - PLUG CONTACTS SHALL PASS A TENSILE PULL PER IEC 60352-2.
 - RoHS AND REACH COMPLIANT

REV.	DESCRIPTION	APPRV	DATE
3	ECN 2023-0123 - ADDED 5 AND 6M LENGTHS	CPD	12/19/2023
2	ECN 2023-0013 - ADDED NSW APPROVAL & 3.5M CORDS	ACG	2/22/2023
1	ECN 2021-0037 - UPDATED TABLES	CPD	5/6/2021

DIMENSIONS ARE IN:	MM [INCH]	APPROVALS		ANDERSON POWER PRODUCTS		
UNLESS OTHERWISE STATED		DRAWN	CPD	2/2/2021	TITLE SDG 2058KH SERIES - SDG400 TO C20 ON RED OR BLUE 12 AWG SJT/ 2.5MM ² H05VV-F	
TOLERANCES:		CHECKED	CHS	3/30/2021		
DECIMALS (INCH)	DECIMALS (MM)	ANGLES	PM APPRV	3/30/2021		
.XX ± .02	.X ± .5	±2°	QC APPRV	3/30/2021		
SURFACE FINISH:		MATERIAL:	UFN	3/30/2021	SIZE [1][2]	
MACHINED 3.2µ [128µin] ✓		SEE TABLE	ENG APPRV	SH	3/30/2021	DWG NO. B02706S1
MOLDED 1.6µ [64µin] ✓		FINISH:				REV. 3
3rd ANGLE PROJECTION		-CAD GENERATED DRAWING- DO NOT MANUALLY UPDATE DO NOT SCALE		SCALE	CADFILE	SHEET
				NONE	05635	1 OF 1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Anderson Power Products:](#)

[2058KH3R5-RED-BK](#) [2058KH3R5-BLUE-BK](#) [2058KH4R5-BK](#)