



Powering Business Worldwide

# 2500Wh Battery Pack Expansion for the GC3000L Portable Power Station

MODEL NUMBER: BPGC2500L



External battery pack provides extended runtime for equipment connected to the GC3000L portable power station in outdoor or indoor applications.

## Features

### Backup Battery Pack Gives Your Compatible Portable Power Station Extended Runtime

The BPGC2500L offers extended battery runtime when used in conjunction with certain Eaton portable power stations, such as the GC3000L (sold separately). It features a lithium iron phosphate battery (LiFePO4) that provides pure sine wave power to connected electronics. Cabling is included.

### Provides Up to 2.5 kWh per Unit

This battery expansion module adds up to 2.5 kWh per unit when connected to a portable power station. When the maximum number of six BPGC2500L battery pack extensions are daisy-chained to a portable power station, a total of 17.5 kWh (including the power station's internal battery) extends runtime for connected equipment. LEDs indicate state of charge (SOC), voltage, temperature, alarm and other status information.

## Specifications

OVERVIEW	
UPC Code	037332286130
Charging Form Factor	Direct Plug-In
Product Type	Portable Power Station
Accessory Type	Battery
Country/Region	North America
INPUT	
Input Phase	Single-Phase
Recommended Electrical Service	120V

## Highlights

- Lithium-ion battery provides pure sine wave power to connected electronics
- Connects to GC3000L portable power station to allow additional runtime
- Adds up to 2.5 kWh per unit for a total of 17.5 kWh (max of 6 battery pack expansions)
- LED indicators provide SOC, voltage, temperature, alarm and other status information

## System Requirements

Compatible with Eaton GC3000L portable power station

## Package Includes

- BPGC2500L 2500Wh Battery Pack Expansion
- External battery cable
- Owner's manual



Powering Business Worldwide

Voltage Compatibility (VDC)	13-45
Input Cord Length (ft.)	2.46
Input Cord Length (m)	0.75
Power Source	Power Cord
<b>OUTPUT</b>	
Pure Sine Wave Output	Yes
Output Receptacles	Hardwire
Overload Protection	Over current protection, over/under voltage protection, short circuit protection, over/under frequency protection Overcurrent protection: current >53A; Effective current > 32.5A; Undervoltage protection: average voltage <170V; Overvoltage protection: average voltage > 276V
<b>BATTERY</b>	
Battery Type	Lithium-ion (LiFePO4)
Expandable Battery Runtime	Yes
DC System Voltage (VDC)	40-57.6
Battery Pack Accessory (Optional)	GC2500L battery pack, expandable to 17.5kWh
Typical Battery Lifespan	4000 cycles
Lithium Batteries	Yes
Capacity (Wh)	2560
Capacity (Ah)	50
<b>VOLTAGE REGULATION</b>	
Overvoltage Correction	Over current protection, over/under voltage protection, short circuit protection, over/under frequency protection Overcurrent protection: current >53A; Effective current > 32.5A; Undervoltage protection: average voltage <170V; Overvoltage protection: average voltage > 276V
<b>CHARGING</b>	
Total Charging Amps	50
Charging Method Detail	Unit must be connected via cable to GC3000L to recharge.
<b>PHYSICAL</b>	
Color	Black
Rack Height	0U
Cooling Method	Air
External Battery Pack Form Factor	Tower
Cable Length (in.)	29.52
Cable Length (cm)	75
Shipping Dimensions (hwd / in.)	22.80 x 13.70 x 13.40
Shipping Dimensions (hwd / cm)	57.91 x 34.80 x 34.04



Powering Business Worldwide

Shipping Weight (lbs.)	63.27
Shipping Weight (kg)	28.70
Unit Dimensions (hwd / in.)	14.000 x 10.600 x 8.860
Unit Dimensions (hwd / cm)	53.6x27.00x22.50
Unit Weight (lbs.)	55.6
Unit Weight (kg)	25.22
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	-4° to 113°F (-20° to 45°C)
Storage Temperature Range	-4° to 113°F (-20° to 45°C)
Operating Humidity Range	10%-85% (non-condensing)
<b>FEATURES &amp; SPECIFICATIONS</b>	
Overcurrent Protection	Yes
Overvoltage Protection	Yes
<b>STANDARDS &amp; COMPLIANCE</b>	
Product Certifications	CAN/CSA-C22.2 No. 62368-1 (Canada); UL 62368-1
Product Compliance	FCC Part 15 Class B (USA); RoHS
<b>WARRANTY &amp; SUPPORT</b>	
Product Warranty Period (Worldwide)	2-year limited warranty

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
<https://tripplite.eaton.com>

© 2025 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.